1 8-3-1973 found huge boulder and long stake (1)
8-29-73 set C/M orig long 1¼"x3' pipe #620905
section corner 8-9-16-17 Eyota 106-12
cert. 8-10-73
5-1877 Hunter P310 No 304 S8 Mike Cassidy, etal.
found stake center road avered by Mr Cassidy
to be where orig corner stood, B trees gone.
- north set stake on line E ¼ S8 and midway and
south side rail road lands. 12.28 ¾ M&L. 811.0'
- also set stake on line E ¼ S8 and midway from
E ¼ S8 and north side R R lands 6.93½ M&L 457.7

8-1898 W Fraser P640 No 576 S16 Decor Bear.
found large boulder stone on top old stake
- meas east 39.95 to small stake set M&L 2636.7
- meas south 39.94 to stone set in wooden culvert 2636.94 N 30 W.

5-1902 Armstrong P46B S4 Alfred Randall, etal
found. stake & stone at this corner used in setting.
SW cor 4. 39.89 E 1/4 4 thru to SW 9
2632.74

8-7-69 J Kerr for Pat. Meas from rod set at 16-17-20-21 (to the meas from east) north apparently did not adjust meas to meas from center crossroads at SW 16 may indicate corner therefore north of center intersection set iron in center crossroads at NW 16 5265.0 R 5265.44
center power pole SE 48.0 — Center 28" oak NE 47.7.
1970 set iron as 1/4 16-17. from exact center 16 over. 1/16 west and doubled exact meas. and this is close to 2629 S. of iron.
record W Fraser. 2636.0

#620905

Card # 2. 8-9-16-17. Eyota 106-12 (2)

8-3-73 dug with tractor = found over 2' of very hard fill then sticky black muck for 2' then gooky clay. - found. 16"x18"x30" boulder with 2½"x 24" oak stake driven well into clay. removed stake and drove 1¼"x36" pipe into hole. dumped bags stone N.W. of pipe with one other stone 14" dia or so with it. did not set anything after filling hole. referenced carefully.
44.6 SE to cone nail in tel pole NES 48.0 To iron set 1968.
77.25 NE to cone nail in tele pole SES 77.25 "
Corner 3.3 south 1.6 east of rod set 8-1968.

OVER.

8-29-73 set CIM over pipe. 2 new Ties.

31.83 SEly to single punch hole in top center S end 18" culv

34.84 NE to same N end

Could not find 1/4 16-17. so reset from line from E. temp. will change slightly to fit all corner concerned

---

set by William Jones 9-1853

80.00 set post at corner to Sect. 8, 9, 16 & 17

Br Oak 4 N 26 W 353

Br Oak 12 N 14½ W 106

Br Oak 15 S 75 E 348

W " 14 S 2½ W 1000