1 7-13-71 set C/M over orig stone #621005 (1)

Section corner 9-10-15-16 Eyola 106-12

10-1872 Hunter P209 No 217 L 10 ½ Harlbert.
found stake center road in line old fence west ½ cor N Bowler.
– Meas east 39.97½ to point set as ¼ corner M & L.
south sec line 10 L 89°55'E. (2638.35'
– 1/16 north set stake M & L. 20.00 N 35'E line east.
– Meas North 10.42 to RR (likely L) then 9.58 to W¼10.
687.72. 632.28.

8-1898 H Fraser P640 No 516 L 16 decar Bear.
found stone and stake as set & located by Hunter P209
– Meas west 39.95 to small stake set M & L as
stat corner corner not to found. L 89½° E. (over)

Co Hwy Dept 1933 B73

2.6' E and 4.8' S of Pet - 33' N of Peter Wood

surveyed Dec 1961 Did not exist

Mean west of line 9 5283.3 Corner iron in place

" east " " 10 5276.8. (or 5271.8) Eastmont Oregon

8-1968 J Kerr Joe and Pat. Meas from rod set as tie rod in center crossroads at NW 16 east. -
set rod as meas tie in center roads N-S-W at NE 16
at 5274.0 R 5273.4 to stone set P209 1872.
- Center PP NW 51.3 - center telegraph SW 67.4.

5-21-1970 Co surv. Meas entire mile SE 10 to SW 10. 5275.07
R. 5277.0 - SE 10 to 1/16 stone 1319.45, set ½" 13' at 2638.9 then
meas 2636.17 to rod - Meas to railroad N 10.42 (687.72) found rod at
685.5 look for stone 2'± west and 2'± south of corner.

Card # 2 9-10-15-16 Eyota 106-12. #621005 (2)

6-30-71 Co surv. 1 mile of road west must soon be graded. figured could easily find recorded stone after so much initial work. found ½" rod set 8-1968 and used 5-1970 also found 1" iron near surface about 2' NE of ½" iron. - dug 2½' x 4' to sub soil base covering all corners with ½" iron in North ⅓ of hole. probed all directions. opened small holes in road SE, SW, N and probed with 4' probe found nothing only small subsoil stones. Corner either gone or lies likely west of area, hard to tell. filled hole and replaced small rod, large rod still in place.

7-6-71. dug entire road with Forrest Wharton cat blade. found stone 10x12x14 with difinate signs stone had been placed as corner. no other stones in area. set 120 D as temp corner. Goes

7-13-71. found 120 D and local reference. set C/M. resting directly on stone, Track. glass. pulled both other iron corners.

92.6 S to 120 D in center road down 2" ✓ ①

39.9 SE to hard nail on NE side tele pole. up 3' ②

56.45 NW to hard nail on NE side power pole. # 486 ③

120 D in road has 1 RP ✓ hard nail W side tele P NNE 76.4

following are reference to other points mentioned.

	large iron found set by Lathelim	½" iron found set 1968 by Sikes.
①	100.0'	98.4.
②	43.83'	44.17.
③		51.3 center pole.

#621005 (9)

Section Corner 9-10-15-16 Eyota 106-12

Set by William Jones 9-1853

80.00 set post at corner to sect. 9, 10, 15 & 16

Br. Oak 6 N 81 E 556

Br " 8 N 10 W 400

Br " 10 S 27½ E 299

Br " 8 S 6 W 408