/ 4-14-79 Set 1/2" pipe #621206 (1)

1/4 corner 11-12 Eyota 106-12
6-1875 Hunter P281 No 278 L 12 Dr 6 Leal. John Buck.
found stake in mound at fence corner
1/16 south Set stake M & L 20.02 1/2 1321.65' for line east.
(with stone on N&S side)
1/16 east set stake M & L. 19.91 1/2 1314.39 for line north.
(note) 1/16 south also had small stones on N & S side of stake

---

9-1891 Thos Fraser P454 No 438 L 14 Charles Alden.
to reset NE cor 14 used stake at 1/4 11-12 and (over
projected line over 1/16 stake with stone on N & S side to set new
cor at NE 14.

3-24-72 Co surv Meas from small pipe set by Tom Ferguson hopefully over C1/4 at 11-12-13-14, North found steel post near where 1/16 corner should be in eye line several posts in brushy fence east at 1322.5 3' snow dug some but didn't find anything and didn't want to destroy any evidence - cont meas north down 20D on W side by willow 6' up over mess of dirt, rocks & brush dozed into area. 2640.3 R Hunter 26433 2 brs Traces 2639.67
true corner if any should be east of willow in line fair fence North (some trash) fence south practically nothing. 2640.3
lines pretty fair with fence west

NE side

7-17-75 Chained 1313.1 from fence post on E side of huge Willow at 1/4 Cor 11-12 East to fence at 1/16 R. Found corner post rotted off. Dug and found base. Set steel post in hole. Found the to be off 1/4 line in 1979 (about 10.4 So. line

#621206 (2)

1/4 Corner 11-12 Eyota 106-12

Set by William Jones 9-1853

40.00 Set post at qr sec corner. deposited charred stake made mound, trench & pits planted cherry seeds SW & NE

4-1979 (1979 Remon. Book Pages 24-25, 35)

4-19-1979 Could not dig at this location - very large (36" double willow) near location. Set a ½" diameter (thinwall) iron pipe 18" long (up 8") on the East side of 36" Willow. Set this on line of old fence posts going North and also to be at double the mean from the cale. Center 12 over the 1/16th fence West and in line with fence West as found

in 1972 (fences South and West now gone). Corner is about 3' East of center of 36" Willow. Set a 1"x4' iron pipe (red colored) about 8" East of the corner as a witness and up ±2'.

4-19-79 1/16th East After measuring E-W 1/4 line of section 12. Found steel post set in 1975 to be 10.37 So of 1/4 line. The C.S. dug from 8' to 12' North of the steel post and from 2' East to 2' West of the fence line North. Dug 18" deep to water. Did not find anything except a ring of fence wire down ±6". Set a steel post (green color) at apprx location of ring of wire which is .57 too far South and .58 too far West of the correct comp. location and is 9.8 N and .5 West of the 1975 point.

June, 1867 H.E. Horton Pg. 86 No 132 shows 1/4 Cor. Meas. West 39.89 chs. to Cor Sec. 11