1 8-8-73 set CIM over stone found. 3 cards. ①
#621605 Bryce T. corner
section corner. 16-17-20-21 Eyota 106-12.
Cor. 1 3-10-75
5-1882 Hunter P377 no 368 L 20 J Hughes, E Cornwell etal.
found stone center road, short stake by side a nered set
by Ben Bear when orig stake was in place, B trees gone.
1/16 west set temp stake N 0 L 19.91½ L 89½ E
To N¼ 20 a stake found & replaced with stone 2x10x22

7-1892 2 loc Fraser P493 no 467 L 21 Dugan, Terry, etal
found boulder stone set by Hunter P377 no mear —

8-1898 H Fraser P640 no 576 L 16 Oscar Bear.
found corner described ~~P640~~ P493.

over)

1/16 north found stake & stone set by Hunter M & L 19.92 (1314.72

1/16 east set stone 2 x 8 x 20 M & L 19.99 (1313.9

1/16 center SW 1/4 16 set stone M & L 19.93 (1314.38 N-S 1/16 line

8-7-68 J Kerr Joe & Pat. Meas from rod set at 1/4 16-21 to hold meas west - rod as 0.0, could not distinguish any 1/16 fences where recorded stone 2 x 8 x 20 would lie left no tie or corner at 1/16 (should have), set rod in center N-S road, 4' south of N edge traveled surface E-W road at 2627.0 R 2626.8 - Marlin P P (NW side) NE 48.55 - Center top F post NW 46.9

5-12-70. set 1/16 north by line & meas from 1/16 stone south of Center 16 over 1/16 stone found at Center SW 1/4 16 which came in open but lands found by reproducing EW 1/16 line. found Center SW 1/4 16 about 1318.2 Record recorded computed 1318.74 stone a boulder - top 8" oval ± accepted center stone.

see card 2

#621605 (2)

Card # 2 16-17-20-21 Cyota 106-12

projected line west equal meas of 1318.2 and dug 4' deep for stone found 1898, found only clean sandy subsoil - set 1"x 2' iron rod - which lines fence west, near center N-S road 35.2 west to center new P pole 41238. (set until proof stones be elsewhere)

- projected line from W 1/4 16-17 over above 1/16 corner which came 2.35' east of rod set in 1968 Lee 8-29-73

also projected line from 1/16 stone & pipe west of center 16 over 1/16 at center SW 1/4 16 found - (meas 1316.0 R - 1315.38) to road south equal meas set 1/2" rod as 1/16 corner until proof stones be elsewhere at 1315.0 - 2'N & road - 116' WSW to CPP east side of drive

also projected line from 1/4 16-21 as set over 1/16 west as set above west intersecting line from north.

(over

line intersected exactly on rod set 1968 - pulled this rod and set 2.35' east on line from north. - new RPs as follows
46.3 NE to pepsi cap NW side telephone pole. NE.
48.5 NW to new black iron corner post center - level road light.
- Note orig meas rod at 1/4 16-21 to rod at corner 5267.0
Meas now corner rod to corner rod (as set) Rd 2625.75 R 2626.8
- Note orig meas rod north to 1/16 fence west 1312.6 R 1314.7
Meas now may be slightly more. 1313.4 ±
- as yet have not dug for 1/4 16-21 or 1/16 west. 5-12-1970.
- Note 1968 meas from 1/16 fence west north of SW 16. north to fence east 2623.5 - 1312.6. or 1310.9 - at 1/4 16-17 as set this 3'± north this fence and 1/16 slightly north of 1/16 fence. this meas near exact of estimate of 1313.4 ±

Card # 3 16-17-20-21 Eyota 106-12 (1/16 east) ③
8-8-73. found 1/16 stone east. 1.95 south 1.15 east
of rod set 5-1970 on projected line over 1/16 stones north.
Meas north 1/2 1/16 line 1315.38 so meas of & 2 1/2 1317.33.
stone a limestone in good vertical position down 2' ±.
#621605
set 3/4" x 20" rod as corner
114.25 W & W To Conc nail by gr. wire stple up 18" PP # 15805
177.6 W NW to PK Nly side tall tele pole
with Cable connection post on south side.
projected exact line west with T-2 transit which
fell 4.85 south of rod set 5-1970.
dug and easily found limestone with small pointed boulder
on north side. Limestone 4.4 south of iron or .45 north of direction
(over

as used limestone as corner driving 1/2" rod between two stones which fell. 0.8 west 4.4 south of iron in place. set C/M over limestone and glass etc.

45.21 SW to Conc nail and bottle cap on N W side PP# 40744

49.58 NE to bottle cap N W side tele Cable pole.

103.15 NNW to SW corner top of main west abutment corner painted red.

8-29-73 found true 1/16 corner north 0.1 W and 2.15 S of iron set 5-1970.

Meas 1314.61 R 1314.72 Cent meas N to iron set

2630.12 R 2629.44 which will be corrected at 1/4 16-17.

RP 1/16 34.63 W to conc. nail in knot on S side PP 41238.

56.47 NW to □ conc nail N E side PP trans pole # 41239.

pulled 1"x24" rod and reset over stake & slag found

#621605 (4)

Section Corner 16-17-20-21 Eyota 106-12

Set by William Jones 9-1853

80.00 set post at corner to sect. 16, 17, 20 & 21

Br. Oak 8 N 77 E 5

Br Oak 8N 62½ W 14

Br Oak 9 S 32 W 38

Br Oak 6 S 12 E 44