8-29-73 dug entire area found no positive Cor. (1)
#6021002

1/4 corner 16-14 Eyola 106-12.

8-1898 W Fraser P640 no576 L16 Oscar Bear corner gone. Mr Bear anera Hunter reset stake with stone at corner which came in log culvert also set 1/16 corner south so reproduced corner from SW 16 over 1/16 corner north 19.92 M & L. (1314.72

set stake & stone 2 x 8 x 28 center road & center log culvert - meas north 39.94. N 20' W (2636.04

1/16 south found stake & stone set by Hunter 19.92 M & L. 1314.72.

1/16 east set stone 2x6x18 M & L. 20.06 1324.1 N 89° 40' W

1/16 to center 16 a stone 2x6x22 set this survey

(over)

1/16 center SW 1/4 16 - set stone M & L 19.93 on N-S 1/16 line.

8-1968 J Kerr Joe and Pat. Meas from tie rod at SW16 North. (tie rod 4' south north edge EW road.) found 1/16 fence west at 1312.6 R 1314.7. Stake & stone, found fence east at 2623.5 fence west at 2628.2. R 2629.4. An rather complex line run in from east ~~one~~ fence cor at center 16 1/16 stone east found. set rod. in center road on this line which came 1.2 south of fence east. this line accepted for east center 16 meas ~~west~~ from wires of fence south at center 16 - center road came at 2640 R. 2648.2, set orig. chainage from east set 20 D nail slightly north of fence east 11' west of 2640, 1½' off road in grass. (tie to chainage. If stone found is 132.1 M & L then center is 2643' east of fence south and due line turned E 1/4 16 by 11.8' center would be 4' south corner post and W 1/4 would come 4'± north of rod set on. about 2626.3 from rod at SW 16. and considerable up to 6' west of E & N S road at W 1/4 16

#621606 (2)

Card # 2. 1/4 16-17 Eyota 106-12

5-8-70 Co surv. - Meas 50' south fence line east and set eight - set 50' south at 1/16 corner east - punched line east and set 46.71 south of Center C/M - Meas west on ℄ line set 1/16 at 1323.12 - Meas west 1323.12 and placed 1/2" rod as corner 53.29 north of random RPs - corner came 3'+ north of fence east and 2'+ south of fence west - corner came 4' west of road. - 6.5' to west edge road, 15' to east edge road - punched cross ○ in west end 24" rock Calc NW 32.45 - " " " " east " " " " NE 38.88 - - corner in low area on east side, high area west side. stone likely gone. RP 1/16 NE Cor Bryce 40 line fence W - 35.2 W To PP 41 2 38

5-12-90 set 3/4" rod as 1/16 south of above 1/4 cor by line and Meas of 1318.2 over 1/16 stones east. see 16-17-20-21.

with 1/4 corner set, 1/16 south as set and SW 16 as set Meas 1313.4± N&L R 1314.7

8-29-73. found rod. set 5-1970 on careful line from center 16 over 1/16 west and doubling mean from center west of 1323.12. R 1324.12. 8-1898 W Fraser.
- dug 4'+ wide 6'+ long to old peat sorbed. May have taken small piece of limestone out with backhoe. but an abandoned gdlv 18" culvert down over 3' and smashed glazed clay tile (est 15") dia down even below bottom of old culvert recorded. believe stone would have been there if galvan & clay tile had not been put in. Corner gone and non-resistant, cattails and bog both sides of road. - reset iron as found and mear south. Electronic at 1/10 S found on digging a stake hole and where bottom of stone set in sandy sub soil
• 1 west and 2.15 south of 1/16 iron set to mear east.
Lee (3)

Card # 3 (3)

1/4 16-17 Eyota 106-12. #6216006

Careful T2 line from C/M at 16-17-20-21. to rod as re set fell .1 east of true 1/16 corner and. elect meas. from 16-17-20-21 1314.61. R 1314.72 while meas from true 1/16 N to reset iron 1315.51 or .9' greater as N-S line of SW1/4 16 much easier and more likely accurate for Jr Fraser to run will set 1/4 16-17 .9' south and .2' west of reset rod. for final corner. not yet re-set

NW to ○ in top center West end 24" galv tube

NE to same east "

RPS when reset.

Set by William Jones 9-1853

2.45 Brook 3lks wide runs NW

8.96 Bbl. Bur. Oak 8 in diam.

27.40 Brook 10lks wide runs West

40.00 Set post at qr sec. Corner

Br. Oak 9 N 1 E 1050

" " 12 S 24E 160

5-2-95 Removed ½" Iron set by Roger Brand in 1973 from Center 16 over 1/16th Corner West of ¼ Cor. Set CIM over ½ Iron on E-W ¼ line from East ¢ on line From sec cor South over 1/16th corner between. The corner is 5½ West of ¢ CR #102. The corner is in line of main fence line West ¢ 10 North of Elec fe line East.

CSD in top of 10"x12" CP ENE 43.55

CSD in gate Post ... S.SW 100.82