X #621805 2 Cards (1)

Section corner- west 18-19 Eyota 106-12
east 13-24 Marion 106-13 David

1-30-1882 Hunter page 372, no. 363 sec. 13 106-13 Proud Corner as "G". Found stone in center of road in line of old fence running south, said to have been planted by mr. Thos. Phelps, a surveyor, when the original cornerstood. All witness trees were gone, so we could not test said stone. "exact quote".
16 cor . west set stake M&L. 19.95 (1316.7' to S¼ sec. 13 which was set from bearing trees.
R°P. 1/16 cor- 18"white oak N27°W 74 lks. (48.84' blazed
6" burr oak S 85° W 42 lks. (27.72' blazed.

6-7-1883 Hunter page 384, no. 375 sec. 19, John Hughes. Corner gone and witness trees all gone, but Mr. O. Manion an old settler, living near the corneryears ago when cor. was a stone set as this corner from orig. stake and that the post and board fence running south was on line with said corner, and that corner post of road fence was set just two rods from the corner, see "G" no. 363, - over

No stone could however now be found, but we took the line of fence and two rods north of corner post as corner. Quote - Meas. east 38.75 (2557.5' then 40.05 (2643.3' to stone entire mile 78.80 chs. or (5200.8'

6- 1893 Wm. Fraser P 512 no. 480 Sec. 18, Willson, Campbell, and Eyota Town Board.

Exact Quote--Found N°E°B°T° properly marked and from that witness tree, according to U.S. gov't notes, located corner drove iron stake as corner.

East--meas entire mile, 78.635 (5189.9'

set iron stake at 9.343/16 chs. 616.57 then set stone at 18.68 3/8 chs,(1233.13' then set stone as 1/4 secs.18-19 at 19.98 3/8 chs or 1318.92' or 2552.05' total 1/2 mile.

--meas. to S.E. corner sec. 18 (a stone found,) 39.96 3/4 chs or 2637.85, or total of 5189.9'

-16 cor north, of 1/64 east 3 set stake M & L 19.90 (1313.4'

--also set stake north of iron at 1/64 th cor. 19.90 (1313.4'

summary of mile Hunter 5200.8 W. Fraser 5189.9 J.K5192.36

east ½ mile H.-2643.3 -- W.F. - 2637.85 J.K. - 2639.26

west ½ mile H. 2557.5 -- W.F. - 2552.05 J.K. - 2553.16

1233.13 1318.92

#621805 (2)

Card # 2. W 18-19 Eyota E 13-24 Marion

10-14-1930 J Kerr B 4 P 12 1930 book # 2 Mut Ben Life Ins Co.
found. S E corner 18 limestone recorded. - ran & meas line west.
found 1/4 18-19. stone no book. # 4 Page 26 No R P S.
found at 2639.2. Hunter P384 2643.3 W Fraser P512. 2637.85
Cont line & meas west found S.W. cor 18. iron stake in small rocks.
Meas S 1/4 to S W 1/4. 2553.16 P383. 2557.5 P512 2552.05

16" burr oak.	N 0° 30' E	34.3.
24" " "	N 33° W	25.3.
10" " "	S 31 1/5' W	49.7.
Corner fence post	S 25° 50' E	36.0

4-1962 J Kerr B 84 P 65 S 24 Melvin Johnson tract W of 1/4 13-24.
ran line from N W cor 24 east, found 1/4 13-24 at 2630.76. - No meas record
R 2633.4 ran Cont line east found 1/16 fence N & T 3943.87 - 1313.11 E of 1/4 cor.

1946 - J. Kerr Bk 30 p. 79
S.W. Cor. Sec. 18 Eyota
Boulder
R.P. - Stump North 149.89'
Transit Tie - set on stump Sight on Peak of barn
Angle To Right 0°58'6.5" 149.59'

4-28-71 Co surv. meas from rod set as SE 18 by line and meas from 1/4 17-18 over 1/16 stone south, true corner until dug out. set P&T at 1242.26 and 2638.06 in line fences N & S. - proj line west to nail in edge B log at 2466.45 or 5104.51
- also set nails at 1320 and 1932.5 (line fe N) no line on either
- found definately blazed BT of 10-1930 (16" brak N0°30'E 34.3 Rec)
- set 3/4 x 10" reinf rod at 2550.0 from 2638.06 or 5188.06.
- corner graded out to bed rock on curve, full meas of 2553.16 would bring bearing to true at least 6° E of true due N, Mag of 34.3 made random slightly south. less than 1°. 2553' would make properly fence north 621.5' R 616.57' Note N.F meas less than J Kerr

#621805 (3)

Section corner W. 18-19 Eyota
E. 13-24 Marion

Gov. Notes 1853 Oct. Ball, Dep. Sur.
North between 19 and 24.
80.00 Set corner post.
(Br. Oak 10 in. N10W 67 lks.) (Br. Oak 12 in. S20W 124 lks.)
(Br. Oak 12 in. N45E 65 lks.) (Br. Oak 8 in. S48E 117 lks.)

6-12-78 (1/64th East) Dug with the backhoe and found a 3/4" square iron driven in bedrock 4' deep
TW. E7.13 S7.08
Iron E9.77 S7.10
6-14-78 Set a 1/2"x2' rod at the road surface over the square iron
9-18-95 CHD SET 5/8" RE ROD
RPs: CSD in W. side of C.P. NNE 57.62
CSD in SSE side pp# 15781 WNW 101.64
Corner in ℄ and 2' W of fence N

W. 18-19 - 6/16/78 Dug with the backhoe on the West side of the iron set in 1971 to cover Will Fraser's measure from the 1/64th East. The Area is in the bottom of the ditch and right on bedrock. Found nothing.

8-4-1981 W 18-19: Set a short 1" sq. pipe with cap driven in bed rock at double the line and measure from the 1/16 East (Fd 1978) over the 1/64 East (Fd 1978) This corner came 2.9 West and .24 South of the iron (removed) set in 1971. This Corner 23.7 North & road a curve.

R.P.: Sp & CSD in West side 18" Bur Oak NNE 34.64