7-11-75 Set C.I.M. over "2"x4" Found 9-5-73
section corner 23-24-25-26 Eyota 106-12. (1)
9-5-73 found wood 2"x4" stake believed true corner.
#622405

6-1913 D Williams P 224 B L25 Mall Keefe
found boulder in center crossroads agreed by
adjacent land owners as being section corner.
Meas south to iron pipe set M&L 2636.5

11-1961 Minn H Dept Du Val.
found sharp pointed boulder - set 3/4" iron riser

44.66	SW	to	MHD disc in 12" oak.
49.53	NW	to	MHD disc in power pole.
48.06	NE	to	MHD disc in power pole.

over

meas South to 3/4" rod set as assumed corner.

2629.0 then 2638 S to SE corner 26 evidently corner in center road intersection. total 5267.0

4-28-71 Co surv. all RPs in place good needle dip

9-5-73 dug extensively with back hoe found rod set. found sub-soil boulder. lying flat which could have been stone accepted, no chance of it being corner as farmers in area full of large stone being in center crossroads which stuck up in road and had to be removed. some 40 year ago. but on further digging found 2"x4" wood. down 2' to top fully 18" long and very vertical could have been placed where stone was

See Card #2.

Card # 2. 23-24-25-26 Cyota 106-12 (2)

2"x4" wood ~~about~~ ~~6~~ 4.5 north ~~6~~ 2.8 east of rod. (removed)

placed dural stone vertical on W side stake, stone very flat on one side which was on bottom when found.



10"x12" bottom, which proves this not true corner.

#622405

48.3 NW to MHD disc on NE side PP. Plumb 2' to mean.

49.53 Du Val

55.3 SW To NW Corner ☐ metal tab bot.

set no corner on rock.

mean - 2"x4" south to true corner. 2639.11
west to cimonet stone 2641.18

when taken NE to MHD disc on S side PP (over) Plumb 2' to mean

elec meas south to limestone at 25-26-35-36 2639.11

elec meas west to C/M at ¼ 23-26 2641.18

elec meas north to C/M at ¼ 23-24 when taken.

7-11-75 Dug down to 2x4 and set rods on East and West sides and C/M on all. Corner lies 4.5 N and 2.8 East MHD rod location (removed 9-5-78)
Corner 4.5 N & E-W road and 2.8 East & N-S road.

R.P.'s

NW corner telephone box SW 55.18

CSD in NW side power pole NE 42.93

CSD in NE side power pole NW 48.30

Spike and C.S.D E side 14" Walnut SW 85.50
(and tree south)

#622405 (3)

Section Corner 23-24-25-26 Eyota 106-12

Set by William Jones 9-1853

80.00 set post at corner to sect. 23, 24, 25 & 26 deposited 3 flint - 2 in. square made mound trench & pits & planted plum seeds NE & SW cherry seeds SE & NW.