6-30-1964 set C/M over 1" steel rod #622805
corner set by mear
section corner. 28-29-32-33 Eyota 106-12.
J. Kerr. 7-1939 P488B, field book 15 pages 126 to 128.
set 1" iron shaft as section corner. as follows.
1/3 mear 2637.33 from 1/4. 28-29 where old stake found.
to S 32-33 where boulder found. and.
5251.52 from SE corner. 28 an orig stone found by
Hunter 1896 set by Mr Bear over orig stake! and.
5265.68
~~5258.44~~ from L stone at SW 29 set by T Fraser
P442 6-1890 who may have erred when he
mear from S 1/4 28 to S 1/4 29 when he assumed S 1/4 28
to be (midway) on S line 28 when E 1/2 line short 8' ±
by Govt Meas.
(over)

6- 1964 J. Kerr setting corner C/M for county.
found pipe set 1939, set C/M over 1" steel rod.
1939 RPS still in place.
~~Cross in north conc headwall~~ Gone. 6-1-73 ~~NE 51.0~~
~~" " south " " " SE 52.0.~~

1964 RPS
punch mark in 4" I beam Culv. end NW. 58.32
Nail in square Alum. Tag in power pole SW. 46.6

Gov. Notes. Oct. 17, 1853
North between sections 32 and 33.
80.00 Set post at corner to sect. 28-29-32-33

April 1, 1863 P.C. Compton pg. 69 No. 97 shows sec. cor.
Y16 North Set (No Meas.)