7-12-65 set C/M. over bridgebolt #622705 (1)

~~to 27-7-8 set ... C30' in place.~~

section corner 29-30-31-32 Eyota 106-12.

5-1890 2hos Fraser P442 No 428 L31 N Weaver, James Campion.

corner stake found but B bros disagreed. He talking about NE 30 now.

meas 2 miles N & south NE 30 to L E 31 159.70'4.

meas 2 miles E & W N'4 31 to N'4 33 159.58½

established corner at prop distances ~~2633.4~~ E & W

set stone 3 x 8/15 x 24. 2635.1 N & S

7-1939 J Kerr P488 B. L28-29-32-33 Town board

found limestone, referenced.

meas east to N'4 33 ~~2629.22 each half mile.~~

7-1965 J Kerr to set corner.

found limestone & bridgebolt riser over RPs

NE corner	conc fence post	NW	53.5
NE corner	old school house	SW	147.8
Disc in cor post	(old RR)	NE	34.65
Disc	power pole	SE	43.25
SE corner	school house (now home)	SW	163.77
NW "	" " "	SW	173.0

1965 meas SE cor 30 to S1/4 30 - 2636.
recorded 2636. P 442.

S1/4 30 to SW 30 2571.0
recorded 2564.3 P 332.

Gov. Notes Oct. 17, 1853
North between sections 31 and32

80.00 Set post at corner to sect. 29-30-31-32

Section Corner 29-30-31-32 Eyota 106-12 (3)
#622905

5-14-79 Took additional reference for road grading.

SE Corner house Fdtn. (top conc. block)
SW 163.70

Punch hole top E end 12" C.M.P.
in driveway on S. side road West WSW181.13

11/61 MHD fd Boulder with 3/4" Pipe & bolt on top east side of road.

RPs conc. fence NE cor. of post NW 46.3'
N½D in fence cor. NE 34.5'
N½D in P.P. SE 43.7'
NE cor. of house SW 47.8'