unrecorded β [3] between # 151 and # 152 for Hanscheid
#630109 (1)

¼ Corner Center 1. Marion 106-13.
8-23-73 found unrecorded missed in covering books.
seems pages may have stuck together.
all corners in NW ¼ Sec 1. June 6 & 7 1873 (T. Hunter
after surveys in Sec 35 and 36 Hanscheid
S36 P205 5. 1872 S35 P2286 1873.
Center 1 " at 3" found stone set by fence post. as
center of section set by Fraser.
ran to W ¼ 1. a stake in mound. set points
at 10.09 665.94. then 10.09 665.94 then 20.18 1331.88
(cor

Meas on north side of NW 1/4 between stones at N 1/4 & NW Cor. found set points from N 1/4 West 1/2 Mile 19.03 1/2. (662.31
then 19.03 1/2. (662.31 Then 20.07. 2649.24 both corners
1324.62. stones.

W 1/4. 1 or 1/4 1-2" found old original 1/4 post standing by side of fence post tested it by stamp of SW (?) B.T. and found the fence post to be correct.

Meas center to W 1/4 40.37 2664.42.
Meas N 1/4 to NW cor. 40.14. 2649.24

5-28-48 John Keer (BK 38, P. 42) Surveyed parcel 325' N-S by 100' E-W in SW Cor NE 1/4 Sec 4. Set Center @ intersection of main Fence lines N-S-E-W. Set Wood stakes at all corners.

#630109 (2)

Center 1, Marion Twp. 106-13

6-15-1982, Center 1: A computed center line using the stake found at the E. ¼ Cor 1 and the iron in pipe at the West ¼ Cor 1 would come 4.49 N. and 3.06 West of the t.n. We dug from a point 3½' North of the t.n., North 3' and West 4½'. (The comp. point comes directly under the N-S fence and in line with the main line of fences E and W) There was 2½' of wasted in fill over natural ground and most old wire. We dug to 4' deep in the South ½ of the hole but came into so many tree roots we didn't have time to dig further. Probed all around. Found nothing.

6-22-1982, 1/64 West: Set up a 1/64 useing the 5/8" rod in pipe at 1/4 Cor 1-2 and stake found at the E 1/4 Cor 1 and the pipe in concrete at the N 1/4 Cor 1 and Taylor pipe at the S 1/4 Cor 1 to comp. a Center 1. The point came 5½' North of the E-W fence. There was no indication here that a fence had ever run North. Dug from this point 5' East and 4½' West. Hole 3' wide at West end and 4' wide at the East end by 2½' deep. Did not find anything.

6-23-1982, 1/16 West: Set up 1/16 useing corners as above for the 1/64. Dug from this point 4' East, 2½' West, by 3' wide by 3' deep. The area had been cut in grading road running NW 1/4 and E 1/4 at this corner. We dug through fill down to natural ground which had been cut almost to clay.

1/4 CORNER CENTER 1 MARION 106-13 #63010 (3)
5/15/87
SET UP TRAV. PT (FROM 1982) FROM TRAV. PT.
80.36 E 1/4 ± DOUBLE BURR OAK 12 1/2' N 1/4. NAIL
WAS GONE, DUG DOWN 1/4 FD STUB OF POST THAT
NAIL HAD BEEN SET BY. DUG FROM NAIL LOCATION
3' ± S. BY 9' + E 1/4. FD KERRS STAKE APPROX.
5.7 E 1/4, 1.2 S 1/4 (THIS STAKE SW COR OF 100'
E-W BY 325' N-S PARCEL IN SW COR NE 1/4
SEC 1 BY KERR IN 1948) TOP OF STAKE DOWN
2' @ BLACK DIRT LINE, SQUARED UP + RUNNING DEEP
INTO BLACK RP'S TO STAKE SPIKE E. SIDE OAK N 4.44
SPIKE S. SIDE BASSWOOD E 13.3

5/16/87 1/64 WEST OF CENTER 1 MARION
OLD PT (COMP 1/64) CAME 6 1/2' N. OF HUGE OAK IN E-W
FENCE. DUG AT E. END OF OLD DIG, THEN SOUTH TO
FENCE & WEST TO TREE, DIGGING TO COVER HUNTERS
MEASURE FROM CENTER OF 1 AS SET BY KERR
IN 1948

1-00

"630109" Cen 01 Marion 106-13

1/2" Pipe w/Cap RLS# 14888 Set by

Vince Fangman at Intersecting Quarter lines