8-7-16 set C.I.M (Corrected of Corner)

~~6-15-65~~ set C/M over iron in place of boulder (1)

Set above ~~quarter stone (West 10.2') probably correct T Water~~

1/4 corner 4-5 Marion 106-13 (#630406

4-1875 Hunter P333 no 327 L4 2r Brackenridge

found stone by post remains in center road in line fence north.

this stone owned by adjacent land owners as replacement

of orig stake. at meas. did not disprove, corner accepted.

- Meas north 39.44 (2603.04' 2599.85 elec. 1972

- 16 east. set stake M&L 20.12 (1327.92

1929 JK. B2 P47. stated stone in place as corner.

- Meas east. 2645.5. No explanation of this meas or corners.

1948 JK. B38 P64. stone marked + and post.

- Meas east 2642.6 set 1/16 1321.3 stone found at

1316.6 not accepted as having been set by surveyor as corner

(over

- Meas south 2643.74. set 1/16 M&L. 1321.87.
- set center SW 1/4 4. - Meas N 1321.72 - W 1322.15

1950 JK. B47-P7 1/16 east steel rod. 1/2" 64' east of fence south.

1952 JK. B55 P69. Meas west. 2643.1 set 1/2" rod M&L.

6-1965 set C/M with iron below. (some dificulty finding stone. corner lies in fence south. Fence line assumed at just as being true line only to be a cattle lane or old road line.
- Dec in massive power pole. as line turns south from power line coming from east (corner pole) E 202.0 S. 42.0
- Hub nail in 28" maple.

Lic Card #2.

Card # 2. 1/4 4-5 Marion 106-13 #630406 (2)

6-1935 County H D. B ~~88~~ 75 P. 8 Kalb, Hellhammer. & 2 inters.
found limestone 2 x 6 x 12 surrounded by small limestone
pieces. - Meas E to Axle 4 corner post 2655.3
47.5 & W to Maple tree 44.6 & E to Maple tree.

11-22-72. found C/M and boulder on top of ground with cross
removed when C/M set 6-1965. probed and found
limestone 2 x 6 x about 12 to 14" broken in two pieces but still
vertical to each part. with at least 10 pieces of limestone around
corner stone which came. 10.7 west and .5 north of C/M.
thus corner exact as Co H D described above 3 Probably Correct Stone
will Zap east to 1/4 3-4, center and 1/16 East.

over.

11-27-72 searched for 1/16 stone east as found by SKell. found fences south with ½" irons by both. East fence of 110' tract is apparent 1/16 fence. West rod not set by SKell. found boulder lying flat on top 6" soil about 1 or 8 feet west of 1/16 fence.

11-21 ran N-S 1/4 line Sec 4. on 35' @ west set iron at Center 4 on corrected West and true E W 1/16 line. after finding limestone at N 1/4 4. reset Center 4 to be on true intersc lines & final corners.

Meas 1/4 4-5 east elec - 2600.8 ± (Ed - 1979 Correction)

Meas 1/4 4-5 (CIM) north to iron at ~~N 4-5~~ elect - ~~2599.85~~ 2603.04.

Record Hunter 4-1875. P333. 39.44

1/4 Corner 4-5 Marion #630406 106-13 (3)

8-9-76 Set ½"x 2' rod on S. side of stone found in 1972. Set CIM over stone. Corner lies in old E-W fence 10.75 W and .65 N of Kerns C.I.M. (removed)

R.P.'s: Spike and Bottle Cap E side of 29" Maple S.W. 38.74

Spike and Bottle Cap W. side of 29" Maple SE 44.46

∴ Mark 3½' above ground on N. side NW 4" steel post of power company storage area E 83.55

over

Oct. 1857 John Fellows Pg. 41 No. 63 Shows Meas. from
1/16 Cor. North 19.56 to North 4-5

Gov't Notes Wm. Jones 1853

39.42 set post + grave stone post, depression
bearing trees, + mound, branch
+ pits planted cherry trees W E + SW