#631309

1/4 corner Center 13 Marion 106-13

1-30-1882 Hunter P372 No 363 L13 Land Prod.

set stake intersection lines from all 1/4 corners

4" Sa Oak S 36 3/4 E 10.5 lks - 4" Sa Oak S 45° W 16 lks.

-16 east set stake M+L 20.03 (1322.0' with BT.

as follows 6" Sa Oak. S 16 1/2° E 26 1/2 lks.

- bearings of center L13 N 0°13' E - N 89°10' W

6-1901 R Fraser P107 No 621 L13 Herman Zumer

stake replaced by corner fence post - tested 60 B blue

-16 west drive stake M+L 19.99 3/4 (1318.3'

-16 south pit stone drive stake M+L 19.91 (1314.06'

T. Ferguson (Dec. 1972) See Back of Note Book File for 2 pages of Notes

Set 1/2" rod by elaborate Trav. and Triangulation

Over

Note: E¼ 13 106-13

Ties: 30p Spk in Blazed 10" Blk Oak N 15°W - 14.65
30p Spk in Blazed 9" Blk Oak N 70°E - 32.40
Center of 12" Blk Oak - East 6.5 (fence around Tree)
30p Spk in Blazed Twin 8" Cherry - S 5°E - 28.34

Center Sec. 13 Set ½" x 30" rod T. Ferguson Dec. 1972

Ties: 30p spike in 12" Blk Oak N.N.E. - 21.75
30p spike in 10" Blk Oak - S.E. - 31.55