#631605 (1)

8-26-63 set CIM over pipe
4-12-78 set CIM.

section corner 16-17-20-21 Marion 106-13

No courthouse records.

7-1943 B27 P30

found corner a 3/4" pipe in center large depression
run line north on section line north 613.5 to road
intersection.

1953 B57P32. Meas west to S 1/4 18 7888.5
accurately found S 1/4 17 stake at 2627.3.

1924 B-7 P14. found stone at 1/16 cor south Wack 1/4 16
west side of SW 1/4 16. Meas S 1321.7 found oak stake
at SW 16. drives deep, set stone with glass etc
run line north set 1/4 16-17 over 1/16 cor. (OVER

8-26-63 set C/M over pipe.

bolt in curb rail of bridge NW 15.22

" " " " " " SW 15.22.

Elec in tele pole N 25.1

C/M now deep 18" ± in black top - riser in place. (non-magnetic) see R.B.
short C/M only way to relocate.

Oct. 1941 A. Armstrong — personal Book 3 p. 53
dug Large hole and found Nothing (set ¾" pipe & stones ~~by Meas. East and by 1320 - 1320 from South~~.)
by Line and Meas. over 1/16 Cor. Stone from North.
Meas. 1315.55' - 1315.55' North
Meas. East To fence post 1324.0'
Meas. South 2634.3 - 2634.3 - Set ¼ Cor. M.t.L.

#631605 (2)

Section Corner 16-17-20-21 Marion 106-13

4-12-78 Dug down and found ~~original~~ CIM monument .65 west and .10 south of nail that was in at the surface. Set a 20" monument over all.

RP's:

- CSD in top center 6"x8" Guard rail post on S.E. cor. bridge S.W. 16.36
- CSD in top center 6"x8" guard rail post on N.E. cor. bridge N.W. 16.49
- CHD dug in E. side telephone pole N. 25.18

May, 1856 Thos. Hunter Pg. 7 No. 11 Shows Sec. Corner 1/16 North 19.90 chs. M&L-B.T.'s (N 68° W 89 lks.) & (S 76° W 50 lks.)

Govt Mks, Wm Jones, 1853 LR

30.00 Set post at corner to Sec 1, 16-17-20-21

Bur Oak 14 N 72 E 154

Bur Oak 15 S 55 E 157

Red Oak 18 S 89 1/4 W 152