7-11-1963 set C/M over iron rod driven thru orig stake ①

#631709

1/4 corner Center 17 Marion 106-13

4-1882 Hunter P376 no 367 S 17 A Stebbins section subdivided survey no 11 P87 Brick Witness tree. found corner past to be true corner.
-16 south set stake M&L 20.01 (1320.66'

3-1946 J Kerr B28 P58 S17 Vern Day.
found fence corner claimed as center section.
distance from west 1/4 17 2642.'

B 33 P 4. Meas north 2649.27

B 49 P 32 Meas north 2649.27 - 1946.2 from NRW 52.

B73 P52 Center 17 north set 1/16 iron at 1324.63. and lot corners south of 1/16 at 311.54 then 310 then 110 to center 52. RP 1/16 north N 21° W 10" brook 5.4' – 11' west of fence.

4-1963 set C/M over rod in orig stake or post corner. steel lot corner N 116.21.
Disc in power pole. W 28.8.
face of square fence post set in concrete NW 11.71

11-1965
B92 P23 Center 17 south, 1/16 or ½" iron rod in line fence east 12' west of fence corner. set N&L. 1321.0 – brass above 1/16 east 2623.0 corners at 1800.17 then 461 then 361.8 to 1/16 on east line S17.

Card # 2

1/4 Corner Center 17 Marion 106-13

#631709

May, 1856 Thos. Hunter pg. 7 No. 11 shows Center Sec.
Bearing Trees to Center Sec. (N 48 3/4° E 65 1/2 lks.) & (S 77 1/4° W 26 lks.)
1/16 North 19.27 chs. m & L - B.T.'s (N 51 1/2° E 27 lks.) & (S 11 3/4° E 8 1/2 lks.)
1/16 South 19.55 chs. M & L. - B.T.'s (N 19 1/2° E 130 lks.) & (S 80 1/4° W 104 lks.)
Meas. East 39.45 chs. To 1/4 Post.
E-W 1/16 line in N.E. 1/4 Meas. 39.65 chs.
E-W 1/16 line in S.E. 1/4 Meas 39.43 chs.