#631809 ①

1/4 corner. Center 18 Marion 106-13

4-1898 2nd Fraser P622 No 565 L18 J Smith, E Keene.
set stone 2 x 8 x 24 at inters lines.
-16 North set stake M & L 20.03 1322.0'
-16 West set stake & stone. 2½ x 10 x 18 on line and
19.98 (1318.68' then 18.87½ 1245.75
-16 east drone stake M & L 20.02 (1318.68'
-16 south set stake and stone boulder. M & L 19.96 (1317.36'
-16 center NW 1/4 set stone. 4 x 9 x 24 at inters lines
-16 center NW 1/4 drone stake M & L 20.01½ on E-W 1/16 line
-16 center SW 1/4 set stake & stone 2½ x 9 x 18 inters lines

(over)

steel rod set in rocky brushy fence line with shell rock very close on high crest No fences N and E. Origin ?

---

corner lies south of ℄ road running west northwesterly. 296.34' there is a steep rise in land from road to corner. Corner is also lot corner of first and second lots with lot lines running south - No references. corner on plat dated 12-1957. noted as stone monument. -1319.21 south to 1/16 corner. B57 P17 - 4-1953

B51 P26 RP to 1/16 cor North ℄ center 18. N & L 1322.83
Center 8" elm AZ 64°40 19.15' - Center 14" Oak AZ 302°30 23.9.
Center 22" elm. AZ 234°35 39.4. 2" pipe.

---

also used N 1/16 corner of S E 1/4 18 ran E. 447.34 staked plat & building sight sold to Harrison detailed.

1/4 Corner Center 18 Marion 106-13 (2)

5-03-89 FD. 1/2" ROD INSIDE 3/4" PIPE PACKED IN LIMESTONE PIECES. #631809

R.P.s : spike & C.S.D. in E side 18" burr oak N 9.43

" " " NE " 16" " " NW 6.31

Iron is approx. 6' E of line of large oaks running S (old fe tree to tree in oaks) & 11' W of center of ditch running N-S