/ 2-5-1973 set C/M over 5/8 x 10" rod.

#632004

1/4 corner 20-29 Marion 106-13.

5-1859 Hunter. P60 no 86 SE 1/4 20, NE 1/4 29.

used corner. - 1/16 points set.

-16 east M&L 20.02 N 89 1/2° W for line north

-16 south M&L 20.00 due North & S. for line east.

-present farm boundary line south - east - west only.

Oct. 1941 A. Armstrong - personal Book 3 p. 53

used Cor. to post as 1/4 Cor.

Meas. East to Sec. Cor. 2642.5'

notice CHD used corner post

over.

2-5-1973 set CIM over 5/8" x 10" reinf rod.
This corner exactly midway 2640.01 but not
on any where near line.
CIM. top at surface of ground level of field North.
MHD dug in N side 4" cedar brace post W 8.0
" " " E " old broken off Cor. P.S. 96

Geo. Hoen, W. Jones, 1973

5/0.0 Set post at point of curve, beyond
chain link fence and creek, 2 pcs. Flint
Chert 5 ft N.E. & S.W.

---

6-15-89
FD. C.I.M. at ground level at fe. intrsctn. E-S-W
C.I.M. is 8.07 E of M.H.D. in bracepost & 9" N of E-W fe.
Set survey marker sign in C.P.