X C.I.M. - set by M.H.D. in fall 1972
#632006

1/4 19-20 Marion 106-13

No records at courthouse.

~~Co~~ MHD Hwy Dept ~~3/4" rod~~ Rod was removed
C.I. set ±6.3' East of rod

disc Willow ~~E 30.2.~~

disc 24" elm. ~~E 84.8~~

9-7-71 ~~found rod~~ rod removed - 1972 in center old road cut along abandoned road.

RP ~~HC~~ 52'± due west to center Minn State bench mark. (1195.411) elev. - MHD.
set 1970 no 5507S

M.H.D - 1971

~~Found 3/4" rod~~ - rod removed rod is 6.28 West of Straight line between Sec. Corners as computed by M.H.D.
See print of Sec. Corner co-ordinates R.B.
Then Inter moved To Point on line & in line fence West

M.H.D. - Fall 1972 - Set C.I.M. in line with fence running West & on Sec. line (actually 0.08' W. of Sec. line)
Copper nail and Disc. in 6" Boxelder - 25.31 - West
fence line running N-S - 4.83 East
nail + Disc. in Cor. fe. post - 4.83 East
nail & Disc in Fe. post - N.N.E. - 15.28
Govt Mon Wm. Jones, 1853
40.00 Set post a quarter section corner, depression
charcoal + mound, brush, + pits + planted
cherry trees W.E + S.W.