5-31-1962. set C/M over pipe in place orig stone. (1)

#632305

section corner 22-23-26-27 Marion 106-13

5-1884 Hunter p 389 no 380 L23 A Anderson and others found stone set by L.W. Lull in mound where orig corner stood.

-16 east set stone M&L. 20.00 for line north which meas 39.92½. (2635.05' to E-W ¼ line.

6-1892. Thos Fraser P 492 no 466. L27 J. Dick, V Bennett found stone P 389.

- meas south 39.85 (2630.1 to temp stake set M&L.
- meas west. 39.96½ (2637.7 to temp stake set M&L.

5-1940 J/Ker B 20 P 33 L27 John O'Neill.

found limestone, set Grey painted boulder on top of limestone Cover

run line south 5261.74 set 1/16 corner at 3946.26
for line west. 2631.4 to 1/16 stone set. — found 1969 (S. center 27)

6-1951 J Kerr. B51 P68 L. 26. Leonard Lietzen.
found boulder - run line south to 1/4 corner found.
set 1/2" rod as 1/16 corner M&L 1315.55 R 1315.05 P492
- meas & run line east 5273.85 set 1/16 at 1318.3 and
found 1/4 corner at 2636.6
- set bridge bolt at Center NW 1/4 26 on E-W 1/16 line M&L 1317.95

5-1962 set CIM over pipe 9-1970 brass cap in new tile pole SE 93.4
Sp tile pole SE 86.6 - Sp power pole west 31.1.
Sp tile pole NE 75.5 - 1/2" x 2' rod - 1' Sq fence W. 100'
lines well with fence west graded centerline grade 1968.

5-1949 B41 P64 L15 run L line 15 set 2" iron staff as 1/16
east of SE 15 1319.3 then iron & brass pipe at 2638.6 run line did
not meas west 1/2 as meas to L 415 tied in. B32 P4 1946.

Section corner 22-23-26-27 Marion 106-13 (2)

#632305

Govt Notes, Wm. Jones, 1853

30. Set post at corner of section 22-23-26-27.

Bur Oak 12 N 77 E 79

" " 11 N 76 W 77

" " 13 S 75 W 205

" " 12 S 61 E 271