X 8-3-77 CIM #683005 #1

section corner. west 30-31 Marion 106-13.
east 25-36 Rock 106-14.

7-1857 Hunter P35 no 56 SE 1/4 25 106-14.
SW 1/4 30 - NW 1/4 31 106-13.

used corner.
-16 - north M & L 19.96.
-16 east on line 18.75 then 20.00 to 1/4 30-31.
-16 south M & L 19.95
-16 center SE 1/4 25 meas N 19.96 E 19.81.
-16 center SW 1/4 30 M & L 19.90 on N-S 1/16 line E 20.00
-16 center NW 1/4 31 meas N 19.96 W 18.92.

June, 1863 P.C. Compton Pg. 72 No 104 shows Sec. Cor,
(see survey for Interior Sec 36 106-14

~~Co Hwy Dept~~ error 25-26-35-36 Rock.
~~stone and pipe~~

– 9-1933 J Kerr. B 9 P 5. ∠ 31 Otto Pasche.
Run & meas line from ∠ W 31 north to stake at
1/16 corner between NW 31 and W¼ 31. 3937.9
1/3 Mile 1312.56. R 1316.7 ~~Hwy~~ R Bhes. N 26¾° W 15
S 68° E 13½.
This Corner in error – possibly should go South some
R.B.

8-3-77 Set a ½" x 2' rod with CIM over. Corner set at double the measure from the W¼ 31 over the E-W fence @ the 1/16th N and at prorated T.H. measured from ¼ Cor 30-31 over the N-S fence at the 1/16 W. Deg from corner So. 1½', No. 3½', W 2½', E 2½' by 3' deep Found nothing. Corner 7' South of S. edge of dry run and in line with old fence N

Section Corner West 30-31 Marion 106-13 #2

East 25-36 Rochester 106-14

#633005

RP's CSD & Spike in 6" Box Elder NE 37.9

CSD & Sp in 14" Box Elder NW 32.14

CSD & Sp in 5" Box Elder NNW 56.89

12/1/80 West Sec. Cor. 30-31, Marion: Set survey marker sign and post 1½' South of the CTM in place.

Cave Nov. Wm Jones 1803

50.00 Set post, and three stones and scribe same to cor. 25, 30, 31, 36 Set in mound of rock.

Plant SE Corr. Range cords. N.E. Marked oak.