X 8-[illegible]77 CIC/P2 #633106 (1)

1/4 Corner west 1/4 31 Marion 106-13
east 1/4 36 Rock 106-14

7-1857 Hunter P35 No 56 & E 1/4 25 106-14
& W 1/4 30 - N W 1/4 31 106-13.

-16 north M & L 19.95
- meas east 38.92

B tree to W 1/4 31 10"B.O N 33° E 1.75 1/2 lks. 175 1/2 lks
10"B.O & 89 1/2 W .49 lks 49 lks

-16 center N W 1/4 31 meas west 18.92 east 20.00

June, 1863 P.C. Compton Pg. 72 No. 104 Shows 1/4 Cor used to set Center Sec 36 at intersecting lines

(over

9- 1933 J Kerr B 9 P 5

set corner on town line between twp corner and 1/16 corner north of W 1/4 31. total 3937.9 2625.34 1312.56

8" burr oak NW 11.0 10" bur oak W 7.0'.

W 1/4 31 as set oak stake 3" long with boulder on S side with notch piled around. Line on south slope of dry run.

Mr John Cockran owns corner post true 1/16 corner - he was present when dry corner set by surveyor.

8-1950 J Kerr B 51 P 3

found stone & stake as referenced. Same witness trees same mear.

- mear south 2625.34

- mens north 1312.56 R 1316.7

Lithrup Nelson - survey to set points on West line. 60 & 8 points fencing.

Gov't notes: Sept. 1853

40.00 ch. set Qr. Sec. Post

Bt.s N 32° E 176 lks. // Bur Oak 10" N 89° W 53 lks.

10" Bur Oak

#633106 (2)

¼ Corner	West ¼	31	Marion	106-13
	East ¼	36	Rochester	106-14

7-77 Found Kerr's Brg. tree and set a nail for electronic traverse. Did not find stake and boulder.

8-3-77 Set a CIC/p2 on the ¼ line from the East and on Hunter tie of 1.76 ch. from the center of the old road East (and also also Hunter shortage of approx 10' per ½ mile from Center 31) Corner falls on So. ditch slope 7' from center of ditch and 23' E of rough line N-S fence and 150' West of old road fence. Corner came 4.74 E and 1.89 So. of traverse nail set from Kerr's R.P.'s. Dug from 2½' E and of t.n. East

for 5', South for 3', and North 1'. Found nothing

R.P.'s

Spike in 10" Burr Oak — N.E. 44.7' (Slope)
spike & disc. in 13" Burr oak — W.N.W. 11.78'
spike & disc in 10" Burr Oak — N.W. 14.91'

Corner Mon. Was Lost 1953

40" Burr Oak (illegible) (Spike)
B. Oak 10 N 32° E 126
" 10 N 53° W 53

12/1/80 W¼ 31: Set a survey marker sign and post 1½' South of CIM in place.