9-2-1965. set CM over orig stone (lowered). #6 33405 (1)

section corner. south 33-34 Marion 106-13
North 3-4 Pleas Grove 105-13

5-1872 Hunter P198 no 205 L 28-33, J Shehan, F Andrews.
found stone in center road planted as section corner.
- Meas west 39.99. - actual 1965 2638.72.
39.85 by Field Book #1 p15-16

6-1877 Hunter P316 no 310 L 33 H Brackenridge.
found stone P198 anered by Mr. G Lucky that he helped place stone in orig mound.
- Meas west 39.99 temp stake M & L.

9-1884 Hunter P 392 no 383 L 3 H Pierson.
found stone P316. (1965 1319.7)
1/16 east set quarry stone with glass around bottom M & L 20.00 3/4.

9-1965 J Kerr to preserve corner.
found large 16" high - 14"x6" bottom - 10x6" top limestone and glass dug stone in so CIM could be placed on top below plow. placed pailfull of crushed rock in depression on top of corner nothing at all within 80 rods to reference to.

9-29-69 J Kerr removed CIM for grading set ½" rod. at exact point of center CIM. as no references near set ½" rod north at about 358° AZ to center of most easterly of 3 hanging insulators ½ mile north - set at 50.0' with bed rail on east side in bean field until corner can be reset. — 11-7-69 reset corner after grading removed 1½ from field north - corner in center new grade. ° ° ° in westend 15" field drive culv. LE 50.98

#633405 (2)

Section Corner | South 33-34 | Marion | 106-13
North 3-4 | Pleasant Grove | 105-13

2-4-1976 Took references to CIM found in ℄ of E-W road and 6' West of fence South
R.P.'s: CSD E. side c.p. SSE 35.97
CSD E. side of most Easterly of pair of Wood posts NNE 31.55
CSD S. side pp # 41507 ENE 136.66

4-28-1976 Co. Surv. - dug with backhoe - hole To N. ℄ W. of CIM. - but found nothing different, will use Kerr's Corner as being Correct. Dug on line of CIM at N 4-5 on next hole found at N¼ Cor 4



Govt Notes, Wm. Jones, 1853

30.-- Dec post & three chord scale ... to Dec. 3-4-33-34. Built mound with trench. Planted S.E. Osage Orange. N.E. Hedge rows.