#642209 (1)

8-22-1963 set C/M ones iron RPD @ LOCATION
7/21/89 FD NO CIM SET SMOOTH
1/4 corner center 22 Rock 106-14 OF 5/8" RPD FD

12-1874 Hunter P266 No 264 S22. D Kennedy.
set marked stake at inters of all 4 1/4 corners.
- Meas north 39.83 = 2628.78
- Meas south. 40.03 = 2641.98
- Capton 9-1886 set stone in place of above stake.

6-1902 Jt Fraser P 20 B S 22. A Markey, J Kelley.
found stone P266.
-16 west set stone M & L 19.90 = 1312.4 to stone set.

4-1905 Ch Armstrong P 90 B S 22-27. town board.
- Meas south 39.94. = 2636.04 Cones

Corner found and used numerous surveys as 1½" pipe

8-1963 set C/M over iron

corner in center line N-S road in line fence each.

–½" rod as property corner. E 33.0.

Spud south side tele pole W & W 31.65

" north " power " N NE 59.85

–16 south set 5/16" ? rod M & L (5/16 rod found by M+B 1318.3 – N ½ ETC 1317.76 S ½ ETC } M+B 9-1973

9-21-1949 Kerr Book 43 p.31

Dug for and found the Center sec. 22, found hole in clay where stake had been pulled, placed 2" pipe at this place & ran random line South – 2637.1 meas. To S¼ 22

4-1954 Kerr Book 57 p.68

Fd 1½" pipe – down 7" R.P.'s spud in T.P. – WSW – 31.62

Meas. E – 2632.2 – N. 2625.48 Spike in PP NNE 59.85

Meas. East M+B – 1976 2630.44

1/4 CORNER CENTER 22 #642209 (2)

7/6/89 FD PK AT SURFACE
7/11/89 DUG WITH JACKHAMMER, FD SPIKE UNDER PK, FD 5/8" ROD
7/21/89 DUG DOWN 13" FD NO CIM, SET SMOOTH ROD AT LOCATION OF 5/8" ROD FD