/ 11-3-69 set pipe as corner in roots dead red oak. #643005 [1]

section corner west 30-31 Rochester 106-14
east 25-36 Salem 106-15

5-1873 Hunter P220 no 224 L36 21 m Dee-L Haskins
Peter Anderson.

found slight mound with stub of stake in it. aveed by mr Wm Dee as true section corner.

1/16 west set temp stake 20.01 N & L. to determine center of 1/4
1/16 south set perm. stake 20.00 N & L
1/16 center NE 1/4 36 set stake inters lines (this line shoved
meas east & west the mean between North and south sides
of NE 1/4 36. - N - 40.02 - L 39.97 - stake set for line south.

8-29-69 JKerr ran & meas line from appro twp corner North

-over-

as yet could not find twp corner dug huge area. found E-W fence about 5285 ± set point at 5280 on 5' offset from orig line no posts only trees to hold fence at corner. backed line from fence west thick line west of road between Sec 36-25 Salem. fence in woods brush very near perfect. dug and scraped some. bulk mean in from west, cannot expect to find stub of stake in mound after 96 years in woods. 24" dead red oak used as anchor tree

9-9-69 Meas west from fence line S (7.3' W random line above) set 3/8 x 14" rod. as 0.0 2' N of fence. Hit projected 1/16 line at 1320.5 and N S fence at 2641 exact record. accepted fence south as E-W line - fence S as line.

11-3-69 drove 1/2" x 5' pipe as corner hit big root in huge dead oak which lies east only inches to west edge tree. figured if tree fell pipe would go - surely a CIM would go. in like manner fence W-E-S.

RPs 60D S side 20" red oak WSW 30° apprx 53.0
60D N " 12" brown oak 6' south of fence west 38.5
center 8" ironed up brown in fence south 6.6

corners as set south 2641.4 to W 1/4 36 - 5282.8 to twp cor.

Section corner West 30-31 Rochester 106-14 L2
East 25-36 Salem 106-15
Govt Mound Knock 1854 #643005
80.00 Set post Lc. corner to Sections 25-30-31-36
Bu Oak 6 S 20 E 31
Bu Oak 5 N 75 E 133