#643104

1

¼ corner south ¼ 31 Rock - 106-14
north ¼ 6 Hi Forest 105-14.

6-1877 Hunter P315 No 309 & 31 J P Dibble.
corner in channel of river - gone. (5179.0) (5225.9)
-meas South section line 3 Carefully 78.47 R 79.18
Making twp corner east to ¼ cor 38.83. (2562.8)
- east set 1/16 cor. Marked stake M & L. 19.82. (1308.1)
set no corner in river but set stake east 87½ lks.
stake south 50 lks and stake north 100 lks.
-16 north set marked stake. M & L 19.98½.

(over)

9-9-69 McGhee assist Roger B.
Meas line west on 150' ⑤ north.
Meas to 1519.9 then triangulated on 2466' base got
total of ~~5159.35~~ To Center miles which was later set 4' west
actual 5163.35 Hanles actual 5179.0 Govt record 5225.9
did not attempt to set line or point at S¼ 31 (impassable).
fences at 1519.9 on 150' ③ near 170'+ very brushy & rough.

T.F. and Pat, April & May 1980, Trav. and Triangulated on N. Line Section 6-105-14 and used Gov't prorated point (by calculation) as ¼ Cor. which comes ± 5' West of fence about 100' North of Sec. line. Used this calc point to set pipe at Center Sec 6-105-14.

Gove Notes M. Kennett 1854
No. 20 Dot post + blaze chained south to quarter section corner. Bears mound + stones. Planted S.E. Osage Orange N.E. Apple Tree.