1 11-4-69 set C/M. over iron rod.
section corner - township corner card in 106-14 SW 31
#G43105
-SW 31 Rock 106-14, SE 36 Salem 106-15.
-NW 6 Hi Forest 105-14, NE 1 Rock Dell 105-15
5-1873 Hunter P220 no 224 S36 Wm Dee - L Haskins
Peter Anderson.
found a foot of old stake in resetting corner from 2B trees
+ 2BT stumps.
- meas north 40.02 to stake in mound. N10°W.
- 1/16 west set perm stake M&L 20.15. S 88°40'E

6-1877 Hunter P315 no 309 S31 J Dibble.
found stake marked. tisted SEBT & SWBT stamp.
- meas east 38.83. To proper dist of S 1/4 3
78.47 to SE 31 gonit 79.18.
79.18 : 78.47 :: 40.00 : 39.64

78.47 5179.0
39.64 2616.2
38.83 (over) 2562.8

3-9-1900 R Fraser P652 No 582½ L6 Hi Forest and Rock Dell Surps.
found township engraved Monument within an inch of road surface in center of cross roads.
- Meas south over run 1½ lks. 40.01½.
see W¼ 6 High Forest.

8-28-69 JKerr Meas from center crossroads west to ¼ fence N 1336
Meas North to ¼ fence east center X roads 1322.3 R 1321.3 R 1329.9
McGhee Surv. Meas line south to corner fence west 2652. R L 641
- dug with tractor 8'x15' covering 8'W 7'E 3'S 5'N of center roads. road N face 5'± west of road south. found clear clay at 3'± no sign of mon.
- later dug west and south area now dug 26+x30+ feet found nothing testimony of Mr Rud and Mr. Alfred Larson that corner once stood well out of ground in road and had to be driven arround. likely bringing to ultimate destruction, could find no mark in clay when set (Leland 2)

Card # 2. Township corner. SW 31 Rock. NW 6 Hi Forest #643105 (2)
SE 36 Salem. NE 4 Rockdell.
disregarded measure to south completely too little evidence
set corner 4' west and 1.6' north of original. 00 in center roads.
lines fair with road north - good with roads East & west and
some 5' west of road south.
- final measurements.
— 1/16 fence north running east 1320.7 near record. and which
is 1/4 distance to NE cor 36. 5284.5 " "
— distance west to S 1/4 36 as set 2660.0 with 1' of record 2659.0
" " to 1/16 fence north 1332
set new chrome 120 D at 1332 in exact line fence north on
exact line between two corners and S 1/4 36 as set.
Mail comes. 3 feet ± north center traveled road.

set C/M with iron below.

Tack cap in power pole #7243	SE	46.13.
" " " corner fence post SE ends	NE	43.09
" " " power pole # 7244 brace	SW	42.3.
SW corner square Tele box	NW	66.65
angle at corner. West to north		88° 49'

Good Wit. Knick 18"

So.. Dec pos to ..... T-p. 105-10c

Wit. ... 14 15

B/K Oak 14 N 37½ W 15c

B.. Oak 10 S 36 E 50

B.. Oak 10 S 45 W 73

B.. Oak 14 N 78½ E 34c

SW 31 ROCHESTER 106-14 (3)
#643105

TOWNSHIP CORNER

10/13/89 FD R.R. SPIKE DOWN 3" IN GRAVEL ROAD.

10/19/89 REMOVED R.R. SPIKE FD CIM DOWN 12"

6-28-93 Turned out June 1992 Ref ∠ of 63° 36' 23" for 184.685'