1 6-12-1972. Corner gone - reset by intersection and ¼ line set ½"x3' rod.
6/31/1984 set C.I.M. over 5/8"x3' rod in place of stone ①
¼ Corner. 2-11 Salem 106-15
#650104

5-1879 Hunter P360 No 351 S2. O'Fallon etal found remains of old stake in line fence north, just north of traveled track owned by Montegue and Malone adjacent land owners as true corner.
set stone 3 x 7 x 13 in its place.
Bearing north N 20° E var. 8°35'E

6-11-70 Co surv. run aerial from N ¼ 2 over C I M at center, used 37.3' ② east for south half mile. fence on top hill, nailed tag post 10 only .65' east of aerial. set ½"x15" rod as S ¼ (temp) on projected line from north and line from C I M at S E cor 2 to center road at hilltop at SW corner 2 location, rod lies south ℄ road. 2.5'

angle of rod as set north to west 90° 23'
R.P.s. Tel cable warning post 6' east of north 40.9
Center 3" steel mail box post WSW 34.9
brass cap in power pole # 8213 NW 62.7
SW corner new house foundation (rock part edge NW 185.3
- no fences south or north close to road - heavy cut on north edge road. slim chance of corner surviving - will dig with tractor.

6-12-72. Co surv. found rod set 6-1970.
dug 8'+ square to clay - road gone - north side cut, steep road slope east - corners & road cannot survive under these circumstances.
- reset rod found with 1/2" x 3' reinf rod. no additional RPS.
- if Center 11 and S 1/4 11 were in or able to reset it would help.
dug 38' long

set by Michael Karrick 6-1854
40.00 set quarter section post in mound with trench, pits, charred stake and Osage Orange Seeds NE & SW.

#650269 (2)

1/4 Corner 2-11, Salem, 106-15

6-13-84, 1/4 Cor 2-11: Dug NE'ly of "½" rod (set 1972) to cover line of fence North and North of ℄ road as recorded by Hunter. Found remaining 7" of dolomite stone, top in old road down 1.2 and shattered. Found good black mark beneath stone well down into clean clay. There was still a few inches of black dirt between the old road and clay. Drove a 5/8" x 3' re-rod where the stone stood and dug the stone down on the south side of the rod. The base of the stone was 4" x 7½". Set a CIM on the rod Corner 6' N of ℄ road E-W and 2½' West of the fence North.

RP's: Bottle cap in ppt # 8213 NW 58.60
West flange cable marker sign (beneath sign)
NNE 31.99