#650309

5-2-1968

1/4 corner Center 3 Salem 106-1E

No records.

5-1968. set 1/2" x 10" rod in black top at true intersd. lines.

corner lies in center County road black top.

- Chisel cut in extreme edge south end galv pipe culv 18" culvert over center - SW 46.1.
- pipe cap. south side power pole. 4' N & W 48.05.
- 1/16 west set 3/4" x 30" pipe N & L 1321.2. to C1M W 1/4 3 over.)

this pipe lies 6" south E-W fence (woven wire) about 2' east of rather poor fence north. ups 4" lies west of enormus willow 20' or so debit measure. corner easy to find in pasture by woven wire fence.

- 1/16 cor center NW 1/4 3 set 1¼ pipe 3' long. on line to 1/16 cor set earlier survey ½" rod. which lies 4' south of south edge pavement and 1' east fence south on tangent this 1/16 pipe lies 2.3' east of N-S fence and 19' north of fence west distance total 2598.96 - 1318.75 and 1280.21

- this E-W 1/16 fence was orig set midway instead of govt prop which accounts for lying south of true line.

May, 1867 H.E. Horton Pg. 83 No. 126 used Center Sec. For breakdown of S.E. 1/4 sec. 3. 1/16 East 20.04 chs M&L 1/16 South 19.98½ chs M&L

(650304) C 6-5-77 mw, RF, AE

(39)

Center 3 106-15 Salem
Found (1/2" rerod) 1/2' west of ℄
CR # 3 and 8' south of line
of Crooked Fence running west.

Set Ref pipe WSW of Corner
on north edge of field drive
50 1/2 west of ℄ CR # 3

T@ Ref pipe
℄Rt P.K. Nail in PP# 8253 (1st pole
North of Corner on west side CR # 3
to Center 3

80° 48' 18"	81° 32' 28"	82° 55' 58"
0° 01' 20"	0° 45' 12"	2° 08' 50"
80° 46' 58"	80° 47' 16	80° 47' 08"

To Center 3 (1/2" rerod)
VA 92° 17' 16"
Slope 50.61 Hor 50.57'