X 9-10-70 set rod over stone found. #650705 (1)
7-3-72. set CIH over iron & stone

section corner west 7-18 Salem 106-15 & D. County 3
10-1884 Hunter P393 No 384 S 6, 7, 18 N Bale etal.
field book 14 p28
corner in 2' road fill. did not look for it.
set stone 6x10x22. at distance 39.88 & 2 mils
North south meas. or midway SW 18 & NW 7.
2 chen meas from S 1/4 7 to 1 mile west 119.54 set stone
corner at distance of gone proportions overrun 45 links, no meas given.

5-1893 H Fraser P508 No 477 S 18 Lawrence, Isaacson Christian.
found stone set by Hunter P393.
- 1/16 east set boulder on line at 19.10 5/8 chen 19.95 5/8 to stone set.
1261.8 1317.1
- 1/16 south set stone 3x8x17. M & L. 19.90 1/2 to stone
4x12x23 set on line & on line fence west by testimony. other

1/16 center NE 1/4 18. set 2 boulder stones at inters lines. found 7-10-70 set ele fence steel post on west side stones - came 1314.35 south of 1/16 north Comp R 1314.72

5-1930 J Kerr S 7 B 3 P 30

set 1/16 stake 1261.54 east of SW cor. T. on line between S 1/4 T and SW cor T "a quote"

- meas north 2639.7. R 2632.08.

- evidently found & used. stone at W sec cor 7-18.

9-1-70 Co surv. meas from C1M at W 6-7 south set nail at 2624.0 found stone 9-4 at 2624.65 - cont south set nail in line fence east at 2629.0 or 5253.65 R 5264.16

- 9-3 meas & run E line south 56.25 from C1M at 1/4 7-18 west found W Fraser stone at 1316.0 R 1317.1 and J Kerr stake at 1318.8 R 1319.65 - nail set on meas from north above total

see card # 2.

Card # 2 W 7-18 Salem 106-15 (2)
#650705

2578.28 R Traver 2578.1 J Kerr 2581.2 set 56.27 line (5) from 1/4 7-18 over stone & Kerr stake - this line fell 66.67 L of nail 2629.0 or 10.4 south of (2639.4) or 5263.4 of stone on that line, as W 1/4 at 2624.65 - W 7-18 must be found before any further line south could even be estimated.

9-10-70 Co Surv. dug for stone found easily 3.1' deep. large + stone fully recorded size with large stake near stone. will set C/M when road settles -

- Cake cap on SE side P pole 8665 SW 81.55
- hard nail in top of ens cor brace post 9 feet N & E 47.9
- corner near on slightly west of center road N & S
- corner found 8.74' South of nail set at 5 2 5 3' from W 6-7 (over) total final mean north 5264.08 5261.74

Meas north in parts 3637.09 to W 1/4 7. then 2624.65 to W 6-7
sun aerial from hub found at W 18-19 to stone found at W 7-18
set nail near line fence at 1/16 south R 1313.67 actual fence line 1305.
- Meas east comp meas to find 2 stones set as center NW 1/4 18 set by
Fraser 1893 at intersection line Comp 1269.5 found stones at 1270.4.
to help find stones meas comp meas from stone found betw N 1/4 18
and W 7-18. 1314.72 found stone at 1314.35.
indicates hub may be foot or so too far west at W 18-19.
- found on corrected aerial line from C/M at 1/4 7-18 to
stone found at W 7-18 that W 9 races stone (now 3/8" rod
with stone below on east side) to be .83' south of direct line
this 1/16 lies 8.0' south & fence east, 2.5 east & fences N & S
- 1/16 center NW 1/4 18 found 2 stones recorded at 1314.35 S
& 1/16 stone north - set ele fence post on west side
came 4.5' south & E-W fence, 22.5' west & fence (North
- 1/16 came 1270.4 east & N-S section line - Stone W 7-18 - hub W 18-19. (2 fences S.).

Card # 3 West 7-18 Salem 106-15
East 12-13 Canales 106-16 (3)
this corner in center of project area search.
condemned final meas. as follows. #650705
-North 2261.74 3637.09 to W 1/4 - 2624.65 to W 6.7 then
both meas were recorded as R 2632.04 total R 5264.08.
- east final total 2578.28 to random mark + 1.24.
total 2579.52 - R 2578.1
W 7-18 stone east to 1/16 stone 1263.52 R 19.10 5/8 on 1261.0
1/16 stone above east to S 1/4 COR N. 1316.0 R 19.45 5/8 on 1317.1
1/16 stone center NW 1/4 18 at inters lines - no meas -
Comp meas south of 1/16 found (north) 1314.72 act 1314.35
Comp meas from above 1/16 west to 1/16 on town line 1269.5
act meas to point on direct line between stone at W 7-18 to
hub found at W 18-19 1270.4 (9-25-70 W 1/4 & W 18-19 not yet set.

4-3-72. Set C/M over ½" x 4' rod. or 5/8 x 12"
found rod set no further RPs.

Set by John Ball 10-1853
74.70 Brick 3 links wide runs NE
80.00 Set post and drove charred stake Corner to Sections
7, 12, 13 and 18 Built mound with trench per instructions
Planted S.E. Osage Orange N E Apple seed.

6-27-69 [illegible]
4' South of Pasture fence East of N. S. Road
148 N of Pasture fence West
20 d.i. Bottle cap in PP 5665 SW 81.48
30 d.i. ~~Spot~~ in mon. post NE 41.55

Section corner. Wnt 7-18 S. line 106-15
East 12-13 Dodge county #650705 | 49

Govt Notes. Ball, 1853

80... Set post & stone & chiseled scribe
corner to sections 7-12-13-18. Built mound
& trench. Planted S.E. Osage Orange.
& N.E. Ash trees.