1 10-13-70 set ½"x7" rod at corrected cor location. (1)
#651709 2

¼ corner center 17 Salem 106-15.
5-1893 W Fraser P 510 no 478 L 17 Nels Jacobsen
– planted stone 5x13x20 at true intersa B Johnson
lines from ¼ corners. J Anderson
– east set stake 8.87 8/9 (586.0), then 8.87 8/9 (586.0) to stone Town board.
set on E-W ¼ line, then 22.17 3/4 (1463.5) to E ¼ 17. a stone. total 2635.5
– 1/16 south set stone 4x12x15 M of L 19.96½ 1317.7

7-1911 Chas Larson P160 B L 20 & 17 Halvor Halvorsen
found stone used in survey of L 20 Mrs Olsen.
likely to locate N ¼ 20 No mea etc.

Co Hwy. B276. 1962.
Meas from E 1/4 17 to ℄ twsp road south R 2635.5
Act 2636.6

2630' from ℄ twsp road south to ℄ road north
for 1/4 17-18. which likely very near 1969 point set
9-22-70 Co surv - set random rail & blacktop & road south.
- meas south set rail at 1319.0 in line fence E & W
- found 1/4 17-20 at 2637.05 R 2635.4
- run line with rail 4.00 came 12.0' E of 1/4 17-20
- dug for 1/16 stone found road worn to bed-rock.
9-24-70 found N 1/4 17 run direct line at 46.03 ② west
from N 1/4 & S 1/4 17. from hill top 1500+ south of Center 17.
- set hard nail on adjusted true line at 2635.4 north of
1/4 17-20 which came 1.65 south of nail in ℄ blacktop.
subject only to possibility of finding N 1/4 17. later

Card # 2 Center 17 salem 106-15' (2)

- 10-1-70 Co surv. found 1/4 17-18 stone after running N-S 1/4 line, and E W 1/4 line from C/M at E 1/4 17 and nail 2635.4 (record) from C/M at 1/4 17-20 #651709
- E-W 1/4 line came .48 south of stone found at 1/4 17-18 Center would be set .24' north by nail now in place as Center 17.
- Meas south now 2635,64 - will reset Rail with C/M

10-13-70 set 1/2" x 7" rod as temp corner .24' N of nail above RP extreme SE corner of long headwall of double span bridge ESE 129.6
" NE " " " " " " " " ENE 129.97
punched cross in west end 3' galv culv of road running south. SW 46.56
corner 1.4' S of & E-W road, about 1.4' E of & road south