/ 11-10-70 set ½" rod as temp corner on inter N-S & E-W lines.
7-3-72 set C/M, over ½" x 3½' iron pipe. #651806 (1)

¼ corner west ¼ 18 Salem 106-15 3

east ¼ 13 Canestio 106-16 D.C.

10-1884 Hunter P 393 no 384 S 6, 7, 18 N Baboetal.

set no corner but on meas west line 18 found

fence line west 39.90 S to W 18-19 then 39.85 north to NW 18

(2633.4) 2630.76 (2630.1) Fraser 2627.46

5-1893 H Fraser P 508 no 477 S 18 A Severts, F Isaacson, A Christian.

searched for corner found none, set stone 4x12x23

on sec line in line fence west offset by A Severts to be in exact line & drive stake when it stood

- meas north 5 lks shorter than to south.

short 14 lks south 19 lks north. over

2630.76 2627.46

1/16 south set stone 6 x 6 x 13 M & L 19.93 (1315.4)
1/16 north set stone 3 x 8 x 17 M & L 19.90½ (1313.7)
1/16 east set stone 3 x 8 x 22 on line and 19.36½
1/16 then 19.95½ To center 18. stone 4 x 12 x 12.
1/16 center NW¼ 18 set 2 boulders at inters lines.

Co H 10. P 276 See ¼ 17-18 for county survey data
RP to 0+00 Sp D Tel pole NE 40.29
Sp D cor FP SE 46.51 – Dec PP SW 38.48
top FP WNW 51.89 set 60 D as 00.
dug considerable deep in center road. – topo against record
Meas J W Fraser indicates stone could be 10.8' ± west.
9-11-70 Meas from rod at 1/16 east & center 18 on exact 1/16 line
N & S from rod north as set at 1317 from west and 120 D
set at midway 1323.7 between SE 18 and S ¼ 18 both CIMS
see Card # 2.

#651806 (2)

Card # 2 W 1/4 18 Salem 106-15
E 1/4 13 Canelco 106-16 Do. Co

- set hard nail on center B'dy at center 18 area at 1320.66 which was record W Fracey 5-1893 (this nail 66.0' east of east side Hugus power pole line south.



- Cont meas west
set hard nail at 1317.0 (record for 1/16 stone west of center)
(this nail 33.85 west of main boundry fence running north.
(9-18-70 run and meas line from 1/16 stone east of W-7-18 and stones found at center NW 1/4 18 set by W Fracer 5-1893 - meas 1314.35 first leg (comp record 1314.72) cont south found nail in road above at 1315.45 - line came .92 west of nail (Could ignore this)
9-11-70 Cont meas west set nail at 1278.1 from above 1/16 nail found it came about .2' west of 120 D set as W 1/4 18 on exact line betw stone at W 7-18 and modern hub found in W 18-19 area

(over

This 120 on line set at 2640.0 from random nail set on line fence east (common land) 120 on line fence west (a recorded witness) - after finding W 7-18 8.74' south of nail, Measured 2631.26 R 2627.4 -

-9-11-70 remeas 120 D south, set nail at 1310.0 To dig for 1/16 corner found total 2627.5 R 2630.8 indicating perpendicular showed to N 2627.76 R 2627.46 — South 2631.05 R 2630.8

dug for both 1/16 corners N + S of W 1/4 18 found bed rock - dug 8' deep for W 1/4 found nothing rock mixed with org road bed beginning 6' deep bedrock - 9' deep stone set C 1/4 3.55 North of 120 D

RP 120 D hard nail & tack org 2640 - 15.35 East

20 D set north at west edge B log north 40.0

hard nail in & and 120 D 90° angle on present N-S line

RP To 40 D set on line as 1/16 south until mean finally computed (1310 & of 120 D)

- center cross cut post of fence W - SW 49.25

- nail in knot on S side southerly of 3 6" cottonwoods in road ditch NW 37.95

see card # 3

Card #3 W 1/4 18 Salem 106-15 #651806 (3)

1/16 north. R 1313.73 M & L. - Meas from orig nail in line/c E
at W 7-18 5253 from C 1/4 at W 6-7. found 1/16 fence W at
1313.5 which moved to 1304.76 from stone at W 7-18
dug for 1/16 stone 10' south found red rock close to surface.
- Meas east to 1/16 stones 1270.4 Comp record 1269.5'
indicating present line as run from stone at W 7-18 and hub
found at W 18-19 close or hub may be little too far west.
- R P to 1304.76 (not line) if not still in place (go 9.09 S & line)
47.85 to center cor post & fe W. - due west
39.15 to punch mark on N side P P 8661 up 2' N W 39.15'
- Correct proportions bring corner at 1313.85 from W 7-18

11-10-70 Co surv. Completed line from C 1/4 as 1/4 7-18
over rail 1.1 north of nail set on random on N-S 1/16 line
see prior notation in red. this line came 4.31 N of 2640 rail

Making Meas North 2640 - 4.31 - 8.74 or 2626.95 to line
" " " south 2627.5 + 4.31 or 2631.81 to hub.

R W Fraser. 2627.46 and 2630.76

- corner comes some 2' west of west edge blacktop mat.
- hard nail in knot on S side 18" pine up 4.5' NE 65.55
- hard nail in knot on N side 16" pine up 4.5' SE 88.47
- hard nail on SE side PP # 8657 up 8' SW 30.81
- hard nail in ℄ N-S road on true E-W ¼ line E 15.37
  with hard nail at edge of mat on straddle exact E-W ¼ line
- new fence line running west (original witness) S 4.3
  ac exact line. E of center 18.
- E-W ¼ line as run came 1.87' south of ⅙ rod, .47' south of nail as center 18, 1.1' north of nail in ℄ as ⅙ W of center.
- very near center blacktop road east

7-3-72 set C/M over ½" X 3½' pipe.

#65180 (4)

1/4 Corner West 1/4 18 Salem 106-15

East 1/4 13 Canestee 106-16 D.Co.

40.00 Set post and drove charred stake for quarter Sec. Cor.
Built mound with trench per instructions Planted, SE
Orange NE Apple Seed Osage

74.70 Brook 3 links wide runs NE