9-3-1974- Set a C.I.P. over a 3/4" x 10" rod N.W. of the cor. post.

#652205

section corner 21-22-27-28 Salem 106-15

3-1878 Hunter P331 no 325 L27 C Johnson - etal

found orig corner in mound at fence corner.

- meas east 40.01 to stone set in place orig stake.

2646.66

3-1895 H Fraser P618 no 561 L 21 J Lillo, H Lillo. O Olen, Lamaland.

found corner P331. set round

boneder ac corner.

-1/10 noah set small stake M & L. 19.93 to stone

3 x 6 x 20 set M & L. 1315.38

8-14-73 - Pat went to corner
visited corner - found a 6x6x12" stone No other
stones in the area - Stone down 10"
created corner by setting it vertical between
the corner posts - set a 3/8" x 4" elec fe. post
beside it.

9-3-1974
Co Surv. went to corner - set a C.I.M. over
a 3/4" x 10" iron rod. We moved the corner slightly
from the 1973 location. in order to set the
C.I.M. meas. E. to 1/4 cor 22-07 = 26.39 ft.

Set by Michael Karrick 6-1854
80.00 Set post for corner to sections 21, 22, 27 & 28 erected mound
with trench pitts charred stake and Osage Orange seeds at
each angle.