/ 10-24-73 set final corner ½"x18" pipe. #652309 (1)

¼ Corner center 23 Salem 106-16.

6-1874 Hunter P254 no 254 S23 S Lilee, Nels Nelson.

set stake true meters lines.

3" jack Oak. S 50° W 1½ lks no other trees near.

-1/16 east set stake 20.09½ M & L N 89° 17' E line south.

-1/16 west set " 20.01 " " line south

6" burroak N 81° E 52½ lks - 6" burroak S 4½° E 108 lks.

-1/16 north set stake 20.00 M & L S 1° E line west.

-1/16 south set temp stake M & L 19.94 line west

-1/16

-1/16 center SW¼ 23 set stake M & L. 19.94 E-W ¼ line.

12-1894 H Fraser P562 no 516 S23 P Sorenson, N Hanson drove stake and set stone at true meters lines. Holtz

over)

--1/16 west - set stone & stake N & L. 20.01. to stone.
6" burr oak S 3° E 111 lks. (found 6-21-72 stone & tree both.
-1/16 east set stake N & L. 20.02 1/2. to limestone.
-1/16 south set stone and stake N & L.
-1/16 center SW 1/4 23 set stone N & L 19.94 1/2 N-S 1/16 line
-1/16 north set stake N & L 19.97 N & L. corner fence post.

6-21-72. found 1/4 22-23 and 1/16 stones east
Meas 1/16 west to 1/4 22-23 without line 1320.66± R 1320.66
Investigated line east to Center 23 Meas roughly on
bearing offset north. Land very rough with Center 23 area in
super steep wooded area showing erosion. Nothing gained
in future search as stones all over line and clear meas.
on 50 foot or more offset (east 1/2) likely less (west 1/2) north would
easily handle line. And likely locate stone (being a W Fraser corner)

#652309 (2)

Card # 2 Center 23 Salem 106-15

9-27-13 found traverse points set in Tom Taylor survey which should place stone if in place 1,3+ south and little west (see field notes) there was a short thick L stone pointed coming to surface. In near exact spot as set 12" ± bottom ± tee stake corner post with L stone on N side and another piece of L stone on N side -

4' S to E-W fence 14' 1 E to N-S fence

~~15.4~~ ~~E~~ ESE to 20 D in root on N side 18" oak wood ac
15.9 Corner support to 4 way fence
17.2 ~~16.6~~ ENE to 20 D N side 16" oak on fence
~~23.5~~ 23.7 ~~25.15~~ NNW to 20 D W side 9" bur oak up 5' - nail to ground slope.

CMD

10-24-73. after setting 1/4 14-23 reset Center 23.
removed stone and iron tee post part set 1/2" x 18" pipe
as corner .52' due West to stone by ri below iron
pipe left pipe up 2" Change in RPs over
a small 1" tree former 5.1 RP now 5.2' due S.