10-23-70 set ½" rod over 1¼"x 3' pipe, orig stone near pipe
6-30-72 set C/M over pipe

#652506 (1) 2

¼ corner 25-26 Salem 106-15

5-1873 Hunter P222 no 225 L25 L Holt E Dwyr.
L Hanson Mc Donnold

found small stake & bearing trees standing
distances correct, bearings S 35½° E instead of record
set new stake in place of old one.
-1/16 north set stake 19.97½ M&L
-1/16 south set stake 19.94 M&L

6-1887 Hunter P 420 no 409 L26 Alice Starkson
found stone set by L A Holt in place of stake set P222
tested B trees still standing.
1/16 west set stake M&L 20.00

(over 1970

10-5-70 Co surv - run & meas line from C1M 1/4 26-27 east set nails at 1309.0 and 2618.0. used nail at 2618 m & as temp line for project. (see center 26)
- Cnit line & meas east with nail at center as 00
- set nail on line as 1/16 E in line fence with 1318.0 R 1320
- set line nail 3' West of Odell Anderson mail box in grass, N edge road.
- set 120 D at 2636, came center north ditch, no fence
road curving to meet Co road 15. No RPS dug some by hand.

10-23-70 Meas from PK at SE 26 north R 1316.04 found 1/16 fence east at 1318.8±, found 2632 came 22.4' south of random nail above - dug for center 26 found stone lying down south edge of road - moved to 1/4 25-26 dug in area indicated by meas from west and south. - found shell rock placed as road fill above muck & soil below. found rather small rounded limestone in wet dark soil in vertical position. No doubt a stone not being corner set as corner described

see card # 2

Card #2 1/4 25-26 Salem 10 6-15. (2)

set 1¼" x 3' pipe deep enough to be below C/M when set
- set ½" rod riser as temp corner #652506
- Meas south to PK as SE 26 2633.75
- Meas west to rod set as Center 26 2638.22 R 2640.
" " to Center (stone found flat) 2617.78 R 2619.54

(road at Center badly eroded, found stone lying flat with dark spot in clay so adjust corner very little to be on true line and recorded proportional distances as above
- 1/16 fence between Center 26 and 1/4 25-26 running south very near 1318+ from Center proving both corners
- PK used as SE 26 meas south 11-1969 which proved 5279+ R 5284+, as PK North 2633.75 R 2632.08. PK could come North some but accepted as is (over)

until proven otherwise. used as is to set 1/4 26-35

RPs Drec on S side most easterly of 3 guard posts E 85.9
- large nail head 2' up on E side PP # 7773 N 32.85
- 40 D as sta 2600. in place on S side road S 33.75
- corner near ℄ road surface at location, lines ℄ road east beyond.
Co H road # 15
6-30-72. found rod set C/M over pipe found below & checked

Set by Michael Karrick 6 1854
40.00 set quarter section post
Black Oak 8 N 30 E 307
Dug Trench