X 10-16-17. Referred stone set M&L 1932 Steel and sand filled hole by Hunter (#1)
9-3-1974 - Set a c I m. over an iron rod at T Hunter's location 3

1/4 corner 27-34 #652704 Salem 106-15.

3-1878 Hunter P331 No 325 & 27 c Johnson et al.

found stake remains with deep hole by side where another witness stake had been driven when pulled out & loose surface dirt filled in hole. aneed by settlers.

- set boulder 8 X 15 x 20 with another stone beneath. with broken stones arround bottom of it.

- 1/10 north set boulder 8 x 12 x 23 M & L. 19.92 1/2 (1315.05'

- 1/10 east corner in gravel knoll being worked out in woodlot set witness stone 8 x 12 x 18 37 1/2 lks N of corner as written. M&L 20.01 1/2

- 1/10 center SE 1/4 27 set stake at intersection lines

(over)

6-7-1932 J Kerr B 8 P14 L 34 Pete Lee

recorded corner could not be found.

run section line 5281.1 set large boulder with broken stone and small stones arround it. stone slightly pointed at top with notch cut in it. stone being irregular in shape & being larger at top & bottom than in the middle (a quartz org).

– 1/16 west set iron M & L. 1320.25

---

10-6-70 Co surv. Meas from 120 D (set in area SE 27 in 1968 on meas from north) west to SW 28 an established corner. set nail in ℄ road N at 2644.0. Meas in ℄ road as existing.

– extended line from N 1/4 27 over center, meas center 27 south selling nail POT 1289.53 – record ℄ 1315.05 M & L came ℄ nail which came at 2625.6 from center 27. and. 3.5' E ℄ 2644' nail

– random line from 120 D at SE 27 and assumed point at SW 27 which is about 5260.5 from area ℄ SE 34 and. 1315 ± from 1/16 fence south ℄ SW 27 this line came 2.55' S ℄ 2625.6. or 2628.15 R 2630.1 will dig for 1/16 north.

#652704 #2

Card # 2 1/4 27-34 Salem 106 15

10-15-70 Co crew dug for 1/16 corner stone north - had line from N 1/4 27 over center 27, set at 1284.53 - found dolomite limestone (Hunter calls same boulder) fully 8x12x23 as recorded at 25.57 S of total of 1315.1 mark 1315.05

- but stone center came 2.38' west of projected line or engraved 4.76 west at S 1/4 27

- ~~S 1/4 27~~ RPS 1/16 - line of N-S fieldpence W 26.7

- Nail in small cherry (near creek) 3" dia NW 40.4

- Center 2" elm tree SW 42.5

- apprx center field drive into farm, east N 145 ±

- corner 4.5' west of road - stone down 16"

- set 3/4 x 11" iron over stone

(over 27-34.)

10-15-70 dug for stone either J Kerr or T Hunter:
- fill about 2' inner muck & peat found 2 boulders 16" long x 8" x 8" aprox did not recognize them as corner as they were heaved and out of position found sandy hole running into peat muck evidently described in 1878 Hunter survey set 1" x 3' iron stake in hole with 2 boulders in E & W sides to hold position of corner (if it truly was corner. Came at about 26300 is very near Correct Meas - Came about 3.00 west of true N-S 1/4 line To came 2.38 west of true N-S 1/4 line
- also found J Kerr stone as described with small stone and piece of iron spring from car leaf spring on from top grade soil set M & L 2640.5 - this stone 3.8' NW Hunters hole with sand and .2' east of 2644' mail and 2626.1 from center 27 R 2630.1
- after finding 26-27-34-35 later found J Kerr stone to east about 2640 to top of stone SE 27 but stone tilted east .7' so more
- must fix stone for C/M set over stone 2639.1'
must decide which corner to set C/M over. both will be recorded saved
SE 27 later moved 6' east (10-28-70) making 2639.7 same as meas west

#652704 #13

Card # 3 1/4 27-34 Salem 106-15

10-16-70 dug and found 27-28-33-34 stone over 8' deep
Came .5 east of nail set 2640 from nail at 1/4 27-34
- as J Kerr corner came .2 east of 2644.0 nail then
Mean J Kerr stone To Stone S W 27 becomes 2639.7
- Hunters sand hole 3.8' south
- found S W 27 to K .78' south of line from S E 27 over center
stone Set by J Kerr. at S 1/4 27 S W & S E corner 27 easy To center stone
at S 1/4 27 very irregular no mark or cross would have to go
.39' south to be on line As Hunter mean would be 2630.1 from
North and sand hole found as 2629.9 & mean corner should be
placed at that point and same E-W as J Kerr stone or .25' west
Johnstone W 1/4 N-S line 3.25' Hunter 3.0'
Summary Cor would be 2639.7 E-W and double mean center to 1/16 d within .2'

as to line from Center 27 and N 1/4 27 as set by county
line would come 2.38' E of 1/16 and 3.25' E of S 1/4 27 as set
- stone found by county as N 1/4 27. (8 X 10 X 18 boulder set by
Hunter 3-1878 P331) claimed not removed. This corner must be
proven first. Center 27 boulder (at least top) found when setting
C I M ignoring S 1/4 27, line from N 1/4 to 1/16 stone would come
1.58 west of center - projecting this line south would be
1.58 - 2.38 - 3.18 or within .07 of 3.25' which is which line
from N 1/4 27 over center C I M would move midway on 2 lines. 27' E.

| | | | | | |
|---|---|---|---|---|---|
| - Nail in cor post fences W & N - NW | S. stone | 48.17 | H hole | ~~51.14~~ 51.23 | |
| - 40 D at edge road, may be hard to find | NE " | 38.63 | " | 41.2 | |
| - Nail in top of 1x2 hub up 8" | S. " | 14.37 | " | 10.61 | |

Set monument 8-30-74 over hub + 3/4 x 18" ± rod
C.S.D. top Center 5" creosoted post (postpainted) S.W. 32.87
C.S.D. corner post N.W. 5.23
Cor. lies 4.6' South & E-W Road + 1' West of ℄ of
Road running North.

#652704 (#4)

1/4 Corner 27-34 Salem 106-15

set by Michael Karrick 6-1854

39.50 Creek 3 lks wide runs North Random line

40.00 Set Quarter Section post in mound with trench pits charred stake and Osage Orange seeds NE & SW - True line

43.95 Creek 4 lks wide runs North