6-20-1966 set C/M over orig stone. #653205 (1)

section corner south 31-32 Salem 106-15
North 5-6 Rock Dell 105-15

6-1895 21 Fraser 579-80 No 529 S17-105-15.
Marcus Wing etal.
found stake in road used in setting NW cor 17 105-15.
- set stone 2x10x18 and stake at corner.
- meas southy 239.55 record 239.85. or.
- 19.85 then 19.97½ then 39.95 5 Chains to SW cor 17 105-15
set no corners until NW cor 17.

- set C/M over stone found 6-1966 for road grade
jot of township.
Record meas from twsp cor west 5277 (orig)

- Meas 1966 from fence south at hwy corner.
1317.8 fence north then 2637.8 to fence then very near
40 chs to stone.

Disc in brace pole of power line	SW	46.87
" " pole.	NW	44.15
"	NW	40.43
" in north end of road culv.	SW	37.3
" " south " " "		

1935 Co H.D. B75 P74. found L stone with flat strap iron beside
- meas east 5293.0 could not find ¼ cor
FP SW 34.6 - also SE 35.0

set by John Ball 10-1853
80.00 set post and drove charred stake corner to section 5, 6, 31 and 32
Built mound with trench per instructions. Planted SE. Osage Orange
NE. Apple seed.