1 11-4-69. set C I M over 3/4" X 12" rod #6536004 (1)

1/4 corner south 1/4 36 Salem 106-15
north 1/4 1 Rock Dell 105-15

5-1873 Hunter P 220 No 224 S 36 Jr Dec, L Haskins
Peter Anderson

found stake claimed to be where orig stake stood in fence line, tested NW BT still standing proved correct. This would make this corner about 2 rods north of direct line twsp cor & SW cor 36. 1°35' would be 36'+

1/16 east set perm stake N & L 20.15 S 88° 40' E

1/16 north set stake N & L 19.76

1/16 center SW 1/4 36 set stake inters lines.

1/16 west set temp stake N & L no distance given N 89 3/4 E (over)

distance should be about 19.93 ±

North line - west 1/2 40.03. west line claimed nearly
E-W 1/4 line " 39.98 straight - N-S 1/4 line straight
so south line " 39.93 ±

4-1876 Hunter P291 No 286 Δ1 Knut Larson found stake under fence P220 used only for setting center Sec 1 Rock Dell

9 and 10 1964 meas line from east center intersection 2664 R2659 at 70' ⊙ each on fence south for near half mile. seems where point set in like old fence south rods correct. Run & meas line from cor post at N 1/4 36 recorded meas 5253.6 all common land no fences to guide line came 45.3 west at south end of line accepted this measure as it put kink in south line of 1°20' not quite record but if corner put in center road would make angle less 1°35' record.
see card #2

#653604 (2)

Card # 2 S 1/4 36 Salem N 1/4 1 Rock Dell.

corner as set (CIN over 3/4 x 12" rod.) lies about 4' south of north edge road about 5' ~~North~~ to E road. in line old fence remains south (all fences in this area very poor shape.) Meas east to township corner as set 2660 ± R2659. Meas north 5253.4' R52536'

RPs. punched cross in east end of farm drive small galv culvert, Meas on slope on ground at corner, 1' high at curb WSW 129.6

— property corner iron 33' north in pile rocks also Corner 208.71 east of above prop corner. (over)

also property corner 208.71 North & C/M on true 1/4 Line
- Note entire section devoid of any real authentic corners, but
Meas. & lines fairly uniform. W'ly 36a recorded stone now
under black top and at least 10' fill.

Set by John Ball 10-1853
40.00 Set post for quarter section Corner
Burr Oak 8 N 47° W 273 links
Burr Oak 5 S 2° W 292 "

10/30/78 1/16th East: Dug from 3' South of Kerb 120d North into the N. Shoulder of road until finally cut phone cable and guide. Found nothing.