6/12/92 County Surveyor fd 1¼" iron shaft #701805 (1)
9/10/92 County Surveyor set C.I.C 1p² in place of shaft

Section corner Cor 13-24 Quincy 107-11 Co line.
10-1896 H^m Fraser P595 no 541. Sec 23-4-5-6 5 parties.
found. S W B T standing rest gone set stake
as corner Corner a "J" P597
Iron bar rak S 35° W 75 lks (49.5'
Mine south 39.76 2624 14 to ¼ corner set M B L.

5-1900 Robt Fraser P679 no 654 sec 24 Drysdale
"found cedar stake driven there by H^m Fraser at which
time I was chainman. Tested said stake from witness
tree standing and found correct. It is 1 foot
west of corner fence post on a rough
Mine north about 15¾ lks 10.4' or 2629.6!

(over)

Gov't notes: 1853

N. 80.00 chains Set Post Corner

B.T's Burr Oak [illegible] S 76° E 87 links
Burr Oak Dia. N 72° E 101 "
Burr Oak [illegible] S 35° W 73 "

6/12/92 County Surveyor fd 1¼" iron shaft with 2" top, 36" long. We dug 1' deep hole all around shaft. There was no sign of post or stake, old notes show stake was 1' west of corner post. The shaft is 1' west of N-S fence, the cond. were mixed up. We dug up to 6' west of trav. nail to cover line of Burrs ref. pipe @ E ¼ 24 ; Lower 1' north to 3' South of trav. nail. We reset the shaft ont. I we can finalize location.

#701805 (2)

SECTION CORNER EAST 13, 24 QUINCY 107-11
6dis/92 County Surveyor went ½ mile east
into W. Nona County (¼ 18,19 107-10 Winona Co.)
Fd 1½" pipe up ± 18" Rp 6.7' South to
center of 24" Bur oak, Ed. Burns, chained
between ¢ 13,24 to ¼ 18,19 37.18 chs (1923) = 2453.88'

9/10/92 County Surveyor Set C.I.C./P² @
location of iron shaft found 6/16/92
Rp's U.S.O. in P.P. #1145' ESE Ed. 29'
N-S fence East 1.0'
Pasture fence running west North 8.0'
Spike & C.S.O. in 12" cherry tree N.N.W. 19.5'
Set S. post 1.0' East of monument