9-11-1974 Found steel Post set by J. Kerr in 1928. set a C.I.M. over the steel post.

X

#711005 ①

section corner 9-10-15-16 Quincy 10 7-11

See field BK 9 P68-79

10-1900 H Fraser P692-8 no 615 & 2-3 9 Partin & 10-11 See NE 2.

corner lost many years. dug rod square, no knowledge or other evidence of corner. set stone 4 x 9 x 30" by good north and south 40.00 ~~39.84~~ ~~5275.38~~ E 39.93 ~~39.93~~ 5282.64 8-976-17 to 10-11-14-15

East and ~~west~~ - E 7393 W 8004

(West 39.98½ - 39.98½)

39.84 2629.44 north & south 3-4-9-10 to ¼ 21-22 final

final N+S 2629.44 - W 79.97 (5278' E 5270.76

1928 J Kerr B-1 P19-22. WF Amos RC Hoelridge:

found large hole where stone had been dug out placed 1" steel post as corner (~~which Amos pulled right out~~) Not True

BPs Sp Cr P & E 25' Sp Tele pole NE 36.2.

Co H D. 1944 B 168 P 16. established nail on P.I. which is 9.0' north of corner used. Dist in PP SW brace P. 58.65
RPS to PI Dist in tele pole NE 28.2.
Dist in tele pole LE 64.5

RPS to corner used (Not described origin 60D nail.
Dist & by in tele pole NE 35.38 - Dist in tele pole LE 56.0
Meas south 5260.7 from corner south

1933 Co H D B 13 P 73 found remains of old stake 2' deep. stake 2"x12" 2.6' E & 4.8 S of PI set hub mold stake.
- Meas west 5282.3 - east 5271.8 - south 2629.7 then 2634.7. used fence running west on 1/4 15-16. RPs Hub NW ~~60~~ 50.2
Tele pole NE 35.0 Fe post north 38.0 (Maybe tie to PI
this corner may have to be reproduced from east C/M SE 10 over S 1/4 10.

9-11-1974 Found J. Kerr's steel post - set a C.I.M. over it. this cor. is 0.95 North of a straight line from the East. S.E. 10 over S 1/4 cor 10.

#711005 (2)

Sec. Cor. 9-10-15-16 Quincy 107-11

9-11-74 (Cont.)

Placed a very crooked steel post beside the CIM as a witness.

R.P.'s

C.S. Disc. South side PP	S.W.	49.30
Top. N.W. cor. conc. cor. post. (across Co. Rd)	S.E.	77.44
C.S.P. W. side Yoke pole stub. (W/box)	N.E.	36.68

GOV. NOTES - 1853 - Wm A JONES

SET SECTION CORNER STAKE 80 chs North of 15-16-21-22 CORNER IN INTERS COUNTY ROADS # 10 W AND S COUNTY ROAD # 2 ELEV 1111 CORNER IN high LEVEL PLATEAU AREA

7/5/90 FD CIM ON NORTH DITCH SLOPE OF C.R. # 2 & C.R. # 10, SET SIGN & POST ± 1' N.W. Cont →

7/5/90 Cont. THE S.W. POLE TIE (19KL) NO LONGER THE SAME POLE Rp's

C.S.D IN P.P. S.W. 51.80'

℄ C.R. #2 ON CURVE S.E. 37.8'

CSD IN TEL. POLE STUB N.E. 36.73'