X 4-2-1973 found large oak post in concrete, ①
3-1991 Pipe & Cap set By R Brand & Assoc.

#711804

¼ Corner 18-19 Clancy 107-11

11-10-1875 Hunter P287 no 283 S19 L H Hamilton
found stake standing, properly marked as ¼ post
owned by Mr L H Hamilton where the original ¼ post stood
witness trees grubbed out and gone.
-16 S set stake marked ¼ corner N14L 19.93 1318.4
to center 19 (a stake set true intersection lines)

11-21 to 24 1892 Thos Fraser P500 no 471 S18 H. J. Davis.
Corner "F" Could find no trace of this ¼ post J Harvey
reported by Hunter, dug entire area where the Mr Purvis
stake used to stand as corner had been gone for 3 years.
set stone 2 x 7 x 17 on line and midway between E & L
this ended not do according to Hunt's proportions shown on plat.



E. 5x10x30.) 5-2½x7x21) F-2x7x17) 7-7x8x14½) L stone) x bent L.S.

8-1/10 north of 7 iron bolt N4L 20 01½ 1321 to iron bolt at 6 which is 1/10 N4L 20 01½ (1321 below center 18 3x15x24 stone and 1/4 17-18 a marked stake by post

1945 Co Hwy Dept B 116 page 55
found flat limestone standing 1.2' N W of corner post of fence N-S-E

GOV. NOTES 1853 WM A JONES

SET 1/4 SECTION CORNER POST 40 LKS WEST OF 17 18-17 20
MEAS MILE 80.12 5287.92 WEST 2647.92 10" BURR OAK S 35 W 213 LKS
CORNER ENTIRELY within one FOOT 140.6
CORNER NEAR high EDGE sharp SLOPE SLOPING
WESTERLY to FLAT DRAINAGE AREA

Card # 2 1/4 18-19 Quincy 107-11 #711804 (2)

4-2-1973 found large oak post in 24" ± dia concrete base in corner woods in level high land de stone likely removed in setting corner post old property fence N & S commonly owned land all sides of corner
- set offset 285' south and ran east, meas east on offset.
- set nail at 1320' and found line 275 from old fence blazed orig line fence no properly urged along evident 4 x 8 x 14½ Cont line east correcting to 285' and set nail in center road at random meas for 17-18-19-20 (see cards)
4-5-73 reset 1/16 east from iron bolts north (see special card) following this card meas non from post incorrected on post
- final meas east to 17-18-19-20 = 2631.4
of 1315.85 chem 1315.55 to acc cor

1/4 COR 18-19 10T-11 QUINCY

6/30/88 DUG TO LOCATE T. HUNTER 1/4 LINE FROM SOUTH WHICH CAME 8' WEST OF C.P TO FENCE N-S-E THE C.P IS NEAR ⊥ FRASER LOCATION, FD 9" X 10" SQUARE POST MARK GOING 1' DOWN INTO CLAY, MARK IS 2.35 WEST OF TRAV. NAIL ; 3.1' NORTH OF T.N DUG TO BOTTOM OF POST MARK, BELOW IT FD SMALLER 2½' DIA. MARK RUNNING SMALLER AS IT WENT DOWN, BOTTOM OF MARK WHICH IS 2' LESS DOWN 2.2' DEEP. DUG FROM 6' WEST OF C.P. TO 12' WEST ; 3' N ; 3 OF FENCE LINE EAST, FD STONE LYING FLAT AT SURFACE 4' W OF COR. POST STONE WAS 1½" X 8" X 14"

6/30/88

1/16TH COR SOUTH OF ¼ COR 18-19 10T-11 DUG FOR T. HUNTER STAKE FD NOTHING ; FROM 5' EAST OF T.N. TO 9' EAST ; FROM 1' NORTH OF T.N TO 4' SOUTH. THE WEST EDGE OF THE HOLE WAS 2½' DEEP TO CLAY ; THE EAST EDGE WAS 1' DEEP TO CLAY, LINE FROM SOUTH WOULD BE ± 8' EAST OF T.N, LINE TO MARK FD AT 1/4 COR 18-19 WOULD BE ± 1' EAST OF T.N

1/4 Cor 18-19 107-11 Quincy #711804 (3)

March 1991 Roger Brand & Assoc. Set Pipe w.th Cap on E-W Section line at Intersection of 1/4 line From north in Section 18 This matches the work of the Co. Surveyor's Traverse the Corner Falls 11' Northerly of C.P. to fence N-S-E.

Note Special Card to follow 1/4 18-19 Quincy 107-11.
711804 F

4-2-73. ran and meas by hand from large corner post. corner on east on 285' apart south. noted pointed stone at 1319.5 under E-W fence., set nail in center road. at 2622.46 Record 2638 11-1892. P500 Thos Frazer.

4-5-73. dug again at 1/16 found recorded stone 4x8x14 1/2 lying at edge of field south of E-W fence. washed out into field went north and found both iron bolts set on N-S 1/16 line by Thos Frazer 11-1892 P500. recorded M & L 1321.0 found two irons 1318.2 apart or 2.8' short in 1/4 mile - saw line carfully south projecting to 3/8" x 4' iron set to replace stone 4x8x14 1/2 washed out.

over.

North iron bolt. M&L betw 1/4 17-18 and center 18. set M&L. 1892 P500. 20.01½ 1321.
- iron with □ head up 3" just North of Concrete base of corner post. (post completely rotted off.)
22.0 SE to 20 D nail on SW side 20" bur oak.
39.8 SW to 60 D nail on NW side 10" walnut.

- iron bolt with ○ head down 10" 1' west of woven wire fence. 1318.2 south of above □ head bolt.
1.8' SEly to steel post in fence. 1st steel post S of Plum hog in fence row which is about 50' long and S edge hog about 50' north of corner.
- ⅜ X 4' iron dr 1/16 betw 1/4 18-19 and 17-18-19-20 set 1318.2 S above. Comes just North of E-W fence 1315.85 E of Final Meas E. 1315.55 1/4. 18-19.