X 10-3-74 Found stone 3" x 7" x 24". Set a 5/8" x 12" rod on the N. side + a 1/2" x 12" rod on the S. side and a C.I.M. over all.

1/4 corner 21 - 28 Quincy 107-11 #712104 (1)

6-1895 Wm Fraser P575 no 526, S16+21, L Lulz

Mr Laird claims in earlier day he & others found orig govt stak and replaced with stone. didnt use this corner in present survey so didnt search for corner.

4-1898 Wm Fraser P625 no 569 S.27, C amos.

found stone in center road used to run in NW cor 28 79.68 1/2 chs for mile. half way would be 39.84 1/2 but Fraser set at 39.87 N 1/4 28 east and 39.81 1/2 N 1/4 27 west for some reason.

2631.42 2627.79

10-3-74

Dug with tractor + found W. Hasers stone 8"x 7"x 24" (with wood pieces) 3' N. of the ℄ E.-W. road + 10' West ℄ of road going North. Stone is 18" deep. Set a 5/8"x 12' rod on the N. side + a 1/2"x 12" iron on the S. side of the stone. Corner is also in line with the fence. South.

R.P's

~~a C.S. disc in N.E. side old cor. post~~ ~~N.W. 38.82~~

C.S. disc in S.E. side New Cor. post N.E. ~~63.14~~ 63.55 (1986)

GOV. NOTES - 1853 - Wm A. JONES

SET 1/4 SECTION CORNER post m+L 40.03 2642'

CORNER IN INTERS twsp roads E-W-N

FARM BOUNDARY LINE SOUTH

CORNER IN MEDIUM SLOPE EAST AND WEST high west.

#712104 (2)

1/4 CORNER 21-28 QUINCY 10T-11

10/88 FOUND CORNER LEANING BADLY

11/3/88 DUG OUT OLD CIM AND REPLACED IT WITH
16" CIM DIRECTLY OVER PT OF STONE FD. (1974)

RP's C.S.D. IN COR. POST N.E. 03.55'
C.S.D. IN EAST SIDE COR. POST SOUTH 30.8