X Oct. 18, 1974 – found L.S. 4"x6"x24"± with Top Section broken off – Set ½" rod on N. side bottom section with CIM over Center of Bottom Section of Stone

section corner 20-21-28-29 Quincy 107-11

6-1895 Wm Fraser P575 no 526 d 16&21, & Lutz found stone center road placed by Mr Laird in early day when all corners were standing.

#712105

— Meas north 40.10 To stone placed by O'Dee this ¼ cor 14½ lks west & 15½ lks south of M&L.

9.57' 10.23'

North 40.10 (2646.6 then 39.79. (2626.14

10-18-1974 Co Surv.
Dug with tractor in E.-W road + in line with fences. Found a 24" long limestone 10" deep. the stone was broken. Drove a ½" rod on the N. side of the bottom piece of stone + set a C.I.M. Over all. Set the top piece of limestone just E of the C.I.M.
Corner falls 2' North ℄ E.-W road + in line with the N.-S fences.

R.P.'s

E.-W. road fence on South side of road	South	30'
E.-W road fence on N. side of road	North	22'
½" x 30" rod under fence South	South	59.4'
Flange on W. side of a 2" fork bar	North	20.55

GOV. NOTES - 1853 - Wm A JONES

SET SECTION CORNER post 80 chs North of 28-29-32-33
CORNER IN prop corner of FARMS IN E-W ~~trail~~ road
CORNER high 1217 IN FAIRLY LEVEL ~ TWSP CREST OF contours