X Oct. 3, 1974 - Set C.I.M. over 5/8 x 15" iron rod # 712.106
Set Corner from B.T. & Line from West. (1)

1/4 corner 20 - 21 Quincy 10N - 11E

6-1895 H Fraser P 575 no 526 S 16-21 H Lietz

Corner missing - found NE BT 6" B.O. N 42° E 296 lks. = 195.36'
which placed Corner about where settler figured corner lay
set stone 3 x 5 x 32. - this corner proved to be 15 1/2 links
North of Midway and 14 1/2 links west of straight line..
Mens south 40.10 (N 5' W) mens north 39.79. (N 5' E)
= 2646.6 = 2626.14'
- placed a stone 36 chains east of above corner on E-W
1/4 line - no center section set.

6-1895 H Fraser P 577 no 527 S 20 J A Watson.
found corner set P 575 (cont over)

Sec 20 cont.

1/16 west - placed stone 3 x 8 x 24 M & L 19.88 1/4 (1312.3)

Oct. 1974 Co. Surv. — dog with Tractor Backhoe did not find W. Fraser Stone, Stone probably Graded Out as road is in Cut of Slope from North. Found 1/16 Stone West Set by W. Fraser in same Survey. also found 1/4 Cor. 19-20 in 1973 — ran line of W 1/4 20 over 1/16 Stone and checked Orig. B.T. N 42°E 296 lks This B.T. location placed Corner about 1.5' short of W. Fraser Meas. from 1/16 Corner. - Used B.T. To place This Corner. Corner lies 3' N. of ℄ E-W Road & ± 2' W. of fence line South.

RP - C.S. Disc in PP # 850 N. W. - 37.03'
40 P in 12" oak with Blaze Mark - North - 72.3'
C.S. Disc in large Cor. fe Post - South 28.35'

1/4 CORNER 20 - 21 Quincy 107-11 #712106 (2)

GOV. NOTES - 1853 - Wm. A JONES

SET 1/4 CORNER post mtl 40 ch. 2640

6" BURR OAK N 42 E 196 LKS 195.4

7" " " S 18 W 204 LKS 134.6

FARM LINES E-W-S common N

CORNER IN LOW AREA betw sharp slopes N + S

ESPECIALLY N where land is like island sharp slope all

ways center ~~top~~ 4 to 6 hundred feet north

top