~~1/4 ROGER BRAND SET PK NAIL AT~~
~~COUNTY SURVEYOR LOCATION~~ 5/29/92 Set 1" sq
712706 PIPE/CAP

1/4 corner 27-28 Aurora 10'7. 11

4-1898 Wm Fraser P625 Ro 567 of 27 C Amoe (1)
set No corner but temp point for line east at
1/5 mean 1/4 21-22 to S 33-34 199.67½ chs or
39.935 chs per taly Mile 2635.71
15" dia Cottonwood due east on east side of road
(Likely near RW line cut 3 Notches in tree

1913 Co HD B1 P57
assumed corner on line E-W fence - no deed
- mens south 26470 to assumed corner

(OVER)

GOV. NOTES - 1853 - WM. A. JONES
SET 1/4 SECTION CORNER POST M&L 40 chs 2640
FARM LINES E W - S
CORNER IN COUNTY blacktop ROAD # 10 N & S

5/27/91 Corner can be set on 1/4 line From East and line From NW 27 to SW 27 Given to Tom Ferguson for survey in NW 1/4 Sec 27

6/27/91 Roger Brand set pk nail for Tom Ferguson at county surveyor location Rps 296.50' NW to chiseled hole in conc culvert.

46.15' ESE TO SPIKE IN NORTH SIDE OF CORNER POST
56.73' WSW TO SPIKE IN NORTH SIDE OF POWER POLE.
5.0' WEST TO E CR #10

1/4 CORNER 27,28 QUINCY 107-11 (2)
#712706
5/29/92 County Surveyor fd PK nail set by Roger Brand & Assoc. Set 1" SQ PIPE/CAP over PK nail. The corner falls 5' east of ℄ C,R#10 & 2' north of main line of fence west. RP's nail with ribbon in north side of PP, WSW 56.66'