#712709

/

1/4 corner Center 27 Quincy 107-11

4-1898 Wm Fraser P625 no 569 S27 C. Amos

set stake and iron at inters of quarter lines "1"

all 1/4 corners used - W 1/4 a North-south measure only

S 1/4 used fence and tree line. stones on E & N corners.

1/16 north - set stone 19.88 3/4 (13 12.58) M&L.

8-18-77 Doubled line and measure of 1/16 th N. Point came in center of 4 corner pot complex to fences N-S-E-W. Set CIC/ρ 20 at this location after digging 5' E-W by 7' N-S 3 1/2' deep to clay fill W.F recorded iron. found nothing.

Field Bk 15 P67-68 at 3 ↑ Robert Fraser set a dry oak stake and ~~1/16th East~~ put a boulde about a foot long on the West side of it mining and on line at 19.96 1/2

5-24-1900 Robert Fraser (P.677 No 602) — Note Fraser's #'s on 2 and 3 on plat do not correspond with explanation below

We will not make a cut on this corner until a Time when it could disagree in section 28
1/4 Cor 27-28 is set since. Will lined from 1/4 Cor 21-22 to S.33-34 (2 1/2 miles) and it is possible that he should have lined from 1/4 Cor 21-22 to Sec Cor 27-28-33-34 taken in the center of the intersection as it is set today or that we should consider the prorated Rd Survey measure from Sec. Cor 27-28-33-34 which could be up to 15 links longer than Rd Survey or 5 to 6' So. of Will oak location