X 5-29-73 set CIM over 1" x 30" iron pipe. ①
corr 3-5-75
#713004

¼ Corner 30-31 Quincy 107-11
10-1874 Hunter P262 no 261 S 31 Peter Scherer etal
corner gone, but on testimony of Mr. Bush & Mr. Krahler
as to plowing for road building & fence location replaced
with stone 2½" x 8" x 22
1317.36 1335.18
1/16 west - set stake 19.96 then 20.23 on line to Sec cor west.
1/16 south - set stone 2 x 8 x 12. 19.96½ M & L. 1317.7 then 20.10'4
mean east 39.85 to section corner. M&L 1326.76 to S¼ 31

5-1887 Thos Fraser P431 no 418 S 30 6 parties - see SW 30
found stone set by Hunter P 262.
1/16 west - set stone 5 x 5 x 18 19.96 then line 20.23 to SW 30
- north 22.46⅔ set stone 3 x 5 x 22 then 17.50 line north to center (over)

Co Hwy Dept 1947 B141 plat Lake P58

hub over stone monument found. iron pipe riser.

Disc	tel pole	N W	43.55	Reset in 1964.			
"	P "	S W	49.83	Disc	T P	N.W	56.54
"	T "	S E	58.75	"	T P	S W	43.3
"	T "	N E	68.22	Disc cor	F P	S E	47.77 or 58.75
				Disc	F P	N E	99.55

found at inter of N-S-E-W roads. flat limestone on end.

Disc north 1482.1 to fractional stone found.

corner in P I Sta 53+21.9 Δ 0°36½ LT going N.

true station 53+21.9 − 149+56 + 100.47 = 5271.56 Co.

Hunter record south 19.96½ M&L 1317.52 x 2

+ " 20.10¼ M&L 1326.76 x 2 = 5288.56 R.

Card # 2 1/4 30-31 Clancy 10 7-11 #713004 (2)

5-29-31 found pipe used by Co H D as corner also recorded limestones at W 30-31 and 1/16 between. - ran and meas elect- over corners and found county iron to be good enough to be final corner, no stone below. final meas W 30-31 to 1/16 stone 1335.38 R 1335, 18 H

see W 1/4 31 for details of 1/16 corner used, etc 1/16 on exact line

meas 1/16 E to 1/4 Cor 1317.62. R 1317 36 H

data south —

GOV. NOTES 1853 - Wm A JONES

SET 1/4 SECTION CORNER post 40 chs WEST of 29 30 31 32

ENTIRE MILE 80 27 5297.82 WEST 1/2 2651 82

WEST 1/16 1337.82

CORNER IN high LEVEL LAND WEST MED - STONE EAST down

CORNER IN 4 WAY ROAD INTERS County Road # 7 N and E (OVER RPS)

43.26 SW to Co disc on near side PP# 39413

37.37 SW to punch hole on top Center S end 24" culv

34.4 NW to punch hole on top battered N end "

57.84 NW to Co disc N side tel pole.

47.93 SE to Co disc SW side corner post

69.4 NE to bottle cap SE side tel pole.

4-17-79 Td CIM OK