1 5-23-73 set C/M over stone found 1¼"x11" iron below stone - C/M rather high ctr 3-6-75 (1)

#713106

¼ corner. West ¼ 31 Quincy 107-11
east ¼ 36 Viola 107-12.

10-1874 Hunter P262 no 261 S31 Peter Scherer etal
corner long gone, no settler ever saw stake or knew about it
set stone 3x4x18. 40.05 M&L. 2643.3

-1/16 south - set stone 3x6x13 running to point 20.02½ M&L.
-1/16 north - set stone 3x 5/13 x24 20.02½ M&L. 1321.65
-1/16 east - set stone 2x4x25 19.86 then 19.92½ to center 31.
1310.76 1315.25
-1/16 center SW¼ 31 - set stone 4x6x18 at true intersection lines
-1/16 center NW¼ 31 - set stone 3x8x15 at true intersection lines.

Gov't notes: Sept 1853 - set Post for Qr. Sec. Cor.
B.T.'s Burr oak 10" S 86° E 217 links
Burr oak 10" N 4½° W 430 "

6-1893 Wm Fraser P517 No 483 & 36 & Urban, Beckital
found stone placed in survey P 262.
-1/16 south found stone P 262
-1/16 north found stone [redacted] } apparently -

5-23-73. easily found recorded limestone, lowered stone
with 1"¼ x 11" solid iron below stone. C/M rather high. may
have had luck. if ever hit by farm machines. gate used.
2.8' E to center bottom of corner post.
6.85' S to bottle cap on E side tele pole.
eye line of tele poles south just east of corner. road entirely
West of township line N-S.
Meas N to 1/16 stone 1321.95' S to 1/16 stone 1321.39. R 1321.65
Meas S to township corner - 1320.0 E to 1/16 stone - 1310.21

Card # 2 W 1/4 31 Quincy 107-11 E 1/4 36 Viola 107-12 (2)
#713106
1/16 corner south of above found recorded size limestone
in center east road ditch just west of west eye line
edge tel poles N 4 S



1/16 corner. North of W 1/4 31. (1)
found. exact size vertical limestone in line 4 way fence.
(gate opening East and south on west side corner post
slt many pieces of concrete and part of iron grate by
corner - Meas 1322.4 ± north, 1321.95 south R 1321.65

1/16 corner south of W 1/4 31 (2)
found exact size vertical limestone as recorded. 10-1874
in center east road ditch just west of eye line of
telephone poles a tele pole south near usual P.O.T
North to south, south of 1/16 corner 106.5'

Card # 3 2W 1/4 31 Quincy 107-11 E 1/4 36 Viola 107-12 (3)

(5) 1/16 corners on W 1/2 Sec 31 Quincy (continued) #713106 1/16 Cor

1/16 corner east of W 1/4 31

found exact size vertical limestone as recorded 10-1874 under fence about 5' ± east of terminal post in fence running E & W in apparent line 1/16 fence 80 rods north

- corner 1310.21 W to 1/4 corner R 1310.76
  1314.89 E to center 31 (N-S 1/4 line as run) R 1315.05
- corner 1323.65 S to 1/16 stone then 1322.7 to 1/16 on town line as set

1/16 corner center S W 1/4 S. 31. Quincy (3)
found exact size limestone. in open field leaning
north apparently hit by plow in times past.
reset lower on exact line 1322.7 S 1323.65 N
- ran ± E-W 1/16 line on 50' (5) south
Nothing to reference to; eye line to distant 1/16 fence
1/2 mile No. a rough eye line from corner to N edge
huge cottonwood near creek in pasture lines with a
steel post - 4ch steel post N'ly from wood corner P I
in fence. this post in small natural swale.

1/16 corner center N W 1/4 31 Quincy (corner .4 too far west) (4)
found. limestone in open pasture S E of fence corner fences
W & N (soon removed completely)
16' E N E to nail in gate post field gate. 5.8' N W to nail in corner P
fences W & N

#713106 (4)

Card # 4 W 1/4 Quincy 31 107-11 E 1/4 36 Viola 107-12

CONT- 1/16 CORNERS & W 1/2 Sec 31 Quincy.

1/16 east of SW 31 township corner (see SW 31).
rod set in blacktop after digging and finding stone lying flat.

1/16 north of 1/16 E of SW 31 or Center SW 1/4 31 Quincy.
5-25 ran N S 1/16 line of S 1/2 Sec 31 from existing corners
found exact size stone leaning slightly being hit by plow.
- put stone on 1/16 line, by placing vertically and adjusting slightly.
Meas N to 1/16 on E-W 1/4 line (final) 1323.65' Elec.
Meas S to 1/16 rod set as 1/16. 1322.7 Elec.

(4) 1/16 corner center of W 1/4. 31. or on N-S 1/16 line W 1/2 31.
found boulder type stone recorded as 3 x 8 x 15 set into
lines in 10-1874 by Hunter Mean roughly from north.
as no corner could be found in corner post area also ran
aerial from 1/16 on N line to 1/16 on E-W 1/4 line, easily found stone
5.8' SE of corner post of fence W & N (north fence to be removed
16' ENE to nail in gate post of random fence running ENE by.

(6) 1/16 corner between W 30-31 and 1/4 30-31 Quincy.
easily found recorded stone on road corner 2' N center road
6' E fence south almost exact line with W 30-31 and 1/4 30-31.
35.6 SSW to nail on E side utility pole. no other RP.
9/25/92 County Surveyor found corner with top
broken off. the rest of mon. seems fine, nailed
Sign to corner post to fences
N-E