/ 7-10-73 set CIM over 16" x 3/4. lag bolt.

1/4 corner 3 - 10 Viola 107-12.
#720304

5-1890 2 Fraser P 441 no 427 S 3 R Johnston

set temp point M & L. 39.78 5/6. 2626.1

- 1/16 east set stone M & L. 19.89 5/12 now Hwy 42.

1313.05

6-29-73. ran section line from 1/2" iron at 2-3-10-11.
by random line. = line fell 7.09 North of rod at 3-4-8-10
re-adjusted line to M & L and dug entire area to Clay.
found nothing - found recent Rail set by outlander
surveyor from Blooming P or somewhere. bad survey.
Govt Notes Cover

1/4 3-10 Viola - 9-9 and 10-1973. Ran and meas S line 3.
Could not find 1/16 stone east of 1/4 3-10 or corner 1/4 3-10
set C I M with 10" x 3/4" □ head lag bolt below M & L.
2623.94
94.1 ENE to Dr Pepper Cap on N side tele pole.
81.55 ESE to conc nail N side PP # 33522.

95.7 WSW to M Dew cap. N side gate or driveway post
of fence east on S side road.
corner. 3' S center road.

Gov't Notes W. A. Jones 1853
40.00 set A temporary section post
Weston true line Between 3 & 10 Bar 8° 42' E
40.02 set A stone corner post in Mound of Earth & Soil
deposited charcoal made trench and pits planted
Osage Orange Stems N & S of trench