6-22-1973 found orig stone down 6 feet - a 6 foot dia culv will cover corner.
7-5-73 set C/M orig 30" x ½" reinf rod. #720404 (1)

1/4 Corner 4 - 9 Viola 10 7 - 12.

10-1894 H Fraser P553 No 510 & 4 E Dickerman

Corner gone, no evidence to locate it.
set stone 5x10x26 M & L. no meas.

1/16 east set temp M & L for line north no meas.

1/16 north set stone M & L no meas.

1/16 center & E ¼ Sec 4 set stone inters lines.

6-14-73 meas east from 1/16 (rail center road inters 00)
to rail center inters at 1/4 4-9.

Meas over.

1193.2 to center rails from 1/16 rail.
1825.1 to eye line fence L. (Sets found .5 east ± fork pole only.
2628.0 to rail center crossroads.

6-22. - Meas elect entire L line sec 4. rail at L W 4 to line rail 3.25' L of orig. 00 rail 2628.08
- dug with tractor found recorded 5 x 10 x 26 stone down 6' to top stone. set bolts and glass & small stones at corner to be covered by huge 6' deformed culvert.

final RPs.
45.55 N E to 2nd staple on Spruce below PP # plat. 20781.
76.65 N.W. to Conc nail in vertical crack on east ly side tele pole.
stone .8' L .38' E of elect 00 rail set on sec line.
Corner originally set N & L (no meas given) See Center 4 for line N 7 1/16.

Card # 2. 1/4 4-9. Viola 10 7-12. #720404 (2)
final on 1/16 stone found north set by 2nd Fraser 10-1894
P553
Meas 1/4 4-9 stone to 1/16 stone 1315.5'
Meas 1/16 stone to drill rod at center 4 (or line nail set due east of drill rod 2.8' set by back-wiggle proving County corner 2.8' too far west and .68' too far south to be correct M & L type corner. (Center 4 not reset)
final Meas S line sec. 4. from stone found .27 E of iron set by Kanzler to stone at 1/4 4-9. 2627.76.
final meas S line sec 4 from stone at 1/4 4-9 to 120 D set over stake or post Pole 4-5-8-9. 2628.17

over

7-5-73 accepted corner as set as final corner.
set C/M over reinf rod line not on A1&L as recorded but within half foot. Took additional RPs all RPs.

45.55 NE to 2nd staple on Spruce below PP plate 20781


76.65 NW to Conc nail in vertical crack on easterly side of tele pole - nail now 1' low of. level to cor

22.6 SE ly to 3/4" hole in end of 5' deformed Culv. other holes there - identified by ·O·

38.75 NW ly to same type hole identified by ·O·

Corner lies 5.25' NE ly from line of holes

52.3 SW to dep punch mark in top center west end of 3'± culvert



Viola 9/4 corner 4-9 #720404 (3)

Gold Notes on reverse side

60ui Notes W.A. Jones 1853
East Random 4of7
40.00 set A temp. section post

West on true line sect 4of7 bar. 8° 30' E
40.00 Set A section post in mound of
earth and soil deposited charcoal
planted Osage Orange seeds N of S of trench