/ 7/26/88 SET 1" SQ PIPE 30" LONG WITH ALUM. CAP 6" BELOW SURFACE #720506 (1)

1/4 corner 5-6 Viola 107-12

12-1893 Hunter P236 no 238 S5-6-7-8 S Horton.
found stone in center road. set as 1/4 corner.
- meas north 40.27 to stone in center road on twp S51E
- meas south 40.00 (2657.82) to stone set this survey. S22'E. line.

11-17-1891 T Fraser P464 no 446 S.6 H & S Miller.
found stone, limestone found by Hunter P236.
1/16 west set stake 19.93 3/8 M & L W'1/4° S.
1/16 north set stone 3x7x17 on line & govt prop distances
19.91 1/4 (1314.22) chest 20.33 1/4 (1341.94) - Govt record 40.42 actual 40.24 1/2
(over)

11-1869-1891 T Fraser P465 No447 S5 L Stinsberg
found corner P464.

1/16 east set stone M & L 19.99 3/8 to temp point set 318.3
intrs lines as center 5 ≡ 10-1894 Captain by T Fraser sets
iron stake as center 5.

1/16 north found corner P464. 19.91 1/2 then 20 33 1/4.

1/16 center NW 1/4 5 stone 2 x 10 x 20 set intrs lines.
line N & S above S10'E — line E & W above N 89°40 W.

1931 Co H D B 62 P 8 cored not find corner stone
assumed corner - Meas south to Section cor 26 49.3
Sp cor P. W. 32.4 — Hub NE 40.1
Meas east to N-S road at 1/16 cor 39.63.0'
Nov. 1, 1974 dug small hole with Tractor, found area cut down
into almost solid rock, did not find stone

V. o/A 1/4 CORNER 5-6 #720506 (2)

Gen Notes on reverse side

7/26/88 DUG SOUTH OF 1974 DIGGING BUT FD BEDROCK 1/2' DEEP

7/28/88 SET 1" SQ PIPE 30" LONG WITH ALUM CAP 6" BELOW SURFACE IN BOTTOM OF DITCH RP's E OF RD NORTH AT RT ∠s TO CURVE NE 28' CORNER IS 7' SOUTH OF FENCELINE WEST, LINES WITH E TWP RD NORTH. C.S.D. IN PP # 42099 N.W. 31.90 Cont on BACK

7/26/88 1/16 WEST OF 1/4 COR. 5/6 DUG FOR STAKE SET BY T. FRASER, FD STONE 3"x7"x18" WITH DARK SPOT BELOW SET 1/2" X 30" RE-ROD ON SOUTH SIDE OF STONE (USE STONE AS CORNER) STONE 4 1/2' WEST OF C.P., MAIN LINE OF FENCE SOUTH IS 1 1/2' EAST OF STONE, OLD BARB WIRE DOWN 1' IS 2' EAST OF STONE, STONE LINES WITH MAIN LINE OF FENCE EAST

Gov't Notes W. A. Jones 1853. 1/4 Cor NTH 5-6

40.00 Set a temp Sec post

South 12' East on true line between 5+6

40.42 Set a Sec post Bur OAK 6 in S 89 E 37 LKS

Made a trench

7/28/88 Cont. SET 1" SQ ON LINE FROM W 1/4 6 OVER THE 16TH STONE FD EAST OF THE CENTER OF SEC. 6 AND DOUBLE THE DISTANCE FROM THE N-S 1/4 LINE OVER THE 1/16TH STONE FD.