/ 11-14-1968 set C/M over 1/2" x 2' rod with glass & track (1)
8-31-79 set C.M. over stake fd.

1/4 corner 32-33 Viola #723306 / 07-12

6-1873 Hunter P 226 No 229 S32 J Madden, C Shellman.
Corner could not be found. ran N-S line set point M & L.
39.84 (2629 ft) but on aver of Mr Williams and others
that orig stake stood 29 feet West of ~~fence~~
~~post~~ placed marked stake Midway and 29 from cor
post putting big hook in line (16.8 ft). ← Not T.H. meas.
— 1/16 west set stake M & L 20.15. To center just run in.

5-1880 John Fraser P 364 No 355 S33 C Derby etal.
found stake above, ~~agreed by settlers~~ Certified to as being correct by J Robinson & Calvert.
1/16 north drone stake set 2 stones M & L 19.81 1/2 (1311.42)
1/16 east set stone 1"x10"x14" likely M & L - 19.93 1/2 bnes)

- Meas south 39.62 compared to Hanlen 39.84½.
2615.0 2629.5

11-14-68 J Kerr. Sec 33 for Jerry Cunningham.
B98 Page 36.

Meas & run N-S line. set rail M & L 2629.77.
setting corner 16.8' east as record would really foul up.
earned 2 80 acre lines east, pulled C/M and set it on
true M & L. making meas - east 2633.65 A
2629.8 R.

Meas North & south 2629.77. A 2629.5 R. by T.H.
Meas west to large angle corner post 2647 ± A 2659.8 R.
Meas east to C/M set Miles line 2633.65 A 2629.7 R.
- C/M set M & L with ½" x 2' rod below corner 4' west of center
traveled road - 5' north line fence west.
- Meas S.E. power pole # 266 5' south & west 29.82.
- Meas N.W. side Tel pole NNE 48.6 — center 18" grade most westerly
NE 90.0 top of bank

Gov't Notes W. A. Jones 1853 Vol A 1/4 (2)
#723306 corner 32-33

1/4 corner 32-33
40.00 set a section post in Mound of Earth
And soil deposits charcoal. Made
trench and pits planted Osage Orange
Seeds E & W of trench

8-31-1979 At 1/4 Cn 32-33: We dug east of Ken's on
line corner since Hunter shown a little east here.
found the remains of an old stake 2' deep and
.4 North and 13.2 East of Ken's CIM (removed).
Set a CIM over a 1/2" x 19" rod driven through the
stake. The corner is 6' North of the fence West
and 8' East of the ℄ N-S road
RP's: Old C.H.D. disc on S. side pp #266 WSW 42.91

to follow W¼ 33 or (¼ 32 33)

1/16 corners of NW¼ of SW¼ Section 33 107-123

-1/16 south of W¼ 33. - ½" rod M&L about 1315'
at normal temp.
came 4' from west edge traveled road. - a rod 33' east.
- 38' To center p.p. NW no 262
- 31' to center large old post stub SW.

-1/16 east of W¼ 33 - ½" x 3' rod M&L 1316.8
came 1' west of fence south - 8' north of fence East
has 2 x 2 x 24 redwood stake just south of rod in low fence

1/16 center SW¼ 33 at inters lines - E-W line run
N-S line computed at 1318' from W 1/16 cor